



Tfca

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: John A. Copeland III
Docket: 10775-36791
Title: NETWORK PORT PROFILING

CERTIFICATE UNDER 37 CFR 1.10

Date of Deposit: August 9, 2005

I hereby certify that this paper or fee is being deposited with the United States Postal Service Mail Post Office To Addressee' service under 37 CFR 1.10 and is addressed to Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

By: 

Name: Wendell A. Peete, Jr.

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Customer No. 24728

Sir:

We are transmitting herewith the attached:

- ☒ Transmittal Sheet containing Certificate of Mailing (1 page)
- ☒ Request For Correction of Record (3 pages)
- ☒ Two Copies of Compact Disc (CD-R) labeled COPY 1 and COPY 2, entitled "Lancop Code.txt Computer Listing"
- ☒ Printout of Computer Program Listing on CD (73 pages)
- ☒ Return postcard

Please send all correspondence to:

Wendell A. Peete, Jr.

MORRIS, MANNING & MARTIN, LLP

1600 Atlanta Financial Center

3343 Peachtree Road NE

Atlanta, Georgia 30326


404-233-700 (Main)

Customer No. 24728

By: 

Name: Wendell A. Peete, Jr.

Reg. No.: 52,108



SN: 10/062,621

PATENT

JFW

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: John A. Copeland, III Examiner: Ronald Baum
Serial No.: 10/062,621 Docket: 10775-36791
Filed: January 31, 2002
Confirmation No.: 2472
Title: Network Port Profiling

CERTIFICATE UNDER 37 CFR 1.10

Date of Deposit: August 9, 2005

I hereby certify that this paper is being deposited with the United States Postal Service Mail Post Office To Addressee' service under 37 CFR 1.10 and is addressed to Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

By: 
Name: Wendell A. Peete, Jr.

REQUEST FOR CORRECTION OF RECORD

Commissioner of Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

Customer No. 24728

Dear Sir:

This request is being filed in order to correct the record of the currently pending application in regard to the submittal of a computer program listing saved and submitted on a first and a second compact disc (CD) in conjunction with the above-referenced patent application; said CDs apparently reported as not being received at the USPTO.

The computer program listing in question was additionally submitted on a first and second CD respectively in related United States non-provisional patent application serial no. 10/000,396 and PCT patent application PCT/US01/45,275, both entitled "Flow-Based Detection of Network Intrusions."

A status inquiry was submitted to the USPTO on March 11, 2005. The purpose of the status inquiry was to obtain an indication of when a communication would be received from the USPTO in regard to the pending application or when the pending application would be examined. Concurrently with the submittal of the status inquiry to

the USPTO a search was made via PAIR of the USPTO file history. A review of the documents posted on PAIR showed that the utility patent application transmittal form submitted in regard to the above-referenced patent application had been stamped with an indicator that the USPTO had not received the CD-ROM copy one and copy two.

A review of our files indicated that the utility patent application transmittal form (attached hereto as Exhibit A) had appropriately been highlighted to specify that a CD-ROM or CD-R was attached in duplicate. A transmittal of computer program listing on CD form (attached hereto as Exhibit B) was submitted specifying therein that two copies of a CD-R compact disc were being submitted, wherein the compact discs were labeled as "Copy 1" and "Copy 2." Further, a return postcard was submitted to the USPTO, wherein conspicuously listed under the "Enclosures" section on the postcard was a statement reporting the transmittal of "Computer Program Listing on CD, copies 1 and copies 2 of a CD with program listing."

On April 20, 2005, a telephone conference was conducted with Examiner Ronald Baum, wherein the subject of the telephone conference was the non-reception of the CDs submitted with the filing of the patent application of the above-referenced matter. During the telephone conference, Examiner Baum suggested that the Applicant resubmit CD copies 1 and 2, in addition to submitting a printout of the computer code that is contained within the submitted CD-Rs.

The Applicant submits that a review of its file indicates that the CD-Rs labeled "Copy 1" and "Copy 2" were believed to have been properly submitted to the USPTO in accordance with the filing practices of Applicant's law firm. In an attempt to correct the present record of the currently pending patent application, as suggested by Examiner Baum, the Applicant hereby submits a printout of the computer code that is contained within the previously submitted CD-Rs. Further, pursuant to 37 C.F.R. § 1.52(a) the Applicant hereby submits herewith two (2) copies of one (1) compact disc (CD-R) entitled "Lancope Code.txt Computer Listing," each in conformance with the International Standards Organization (ISO) 9660 Standard, with the contents in compliance with the American Standard Code for Information Exchange (ASCII), enclosed in a hard compact case within an unsealed padded and protected mailing

envelope, labeled as "Copy 1" and "Copy 2", accompanied by this transmittal letter, as required by said Rule.

In accordance with 37 C.F.R. § 1.52(e)(3)(ii), the operating system compatibility for the files contained herein are in the Microsoft Windows NT Operating System, and the CD-R includes the following ASCII text file contained on the compact disc, including the file's name, size in bytes, and date of creation, as follows:

| DATE OF CREATION | SIZE IN BYTES | FILE NAME |
|---------------------|------------------|------------------|
| Jan. 30, 2002 | 154,450 | LANcope Code.txt |


Pursuant to 37 C.F.R. § 1.52(e)(4), Applicant hereby states that the two compact discs identified as "Copy 1" and "Copy 2" are identical.

In accordance with 37 C.F.R. § 1.52(e)(6), each CD "Copy 1" and "Copy 2" is labeled with information indicating the name of the inventor, title of the invention, Applicant's docket number, the creation date of the compact disc (January 30, 2002), and an indication whether such copy is "Copy 1" or "Copy 2".

Applicant has made a bona fide attempt to correct the record in regard to the presently pending patent application. If any condition remains incomplete, then Applicant kindly requests that the undersigned be contacted at the address or telephone number shown below so that such condition may be met.

Respectfully submitted,

MORRIS, MANNING & MARTIN, LLP



Wendell A. Peete, Jr.

Reg. No. 52,108

August 9, 2005

MORRIS, MANNING & MARTIN, L.L.P.
1600 Atlanta Financial Center
3343 Peachtree Road, N.E.
Atlanta, Georgia 30326
404-233-7000 Main
404-495-3682 Direct
Customer No. 24728

Readme

FILE INDEX FOR FILES ACCOMPANYING THE PATENT APPLICATION OF

John Copeland
"Network Port Profiling"

Filed January 30, 2002

NOTICE OF COPYRIGHT

A portion of this disclosure of this patent document contains material that is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

All files are in ASCII (text) format and saved with ".txt" file suffix. All files can be opened in Microsoft WORD 97, within WINDOWS NT.

All files are originally C code files.

Note that the "date of creation" listed below of the files is the date on which the files were created for the purpose of inclusion on this CD-ROM; the date is NOT the date on which the contents of such files were created.

There is 1 file, not including this file:

| Size in Bytes | Date | File Name |
|------------------|------------------|------------------|
| 154,450 | January 30, 2001 | LANcope Code.txt |

```

                                LANcope Code
#define _REENTRANT // basic 2-lines for threads
#include <pthread.h> // compile gcc -lpthread -fvolatile -global
#include <time.h> // assumes service is same as port
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/types.h>
#include <sys/stat.h>
#include <signal.h>

// lancope 000527 Thread 1 collects packet header and sorts into flows (from
ipselect.c 991215)
// Compile: gcc lancope.c -O3 -pthread -fvolatile -fvolatile-global -o lancope
// MUTEX order: none -> flows -> hosts -> pairs -> bs
// You can skip a lock going to the right, but NEVER go left without unlocking
higher db's

char progid[100] = "LANcope by John Copeland 9/28/00, copyright 2000, all rights
reserved";
FILE *infile, *log_flow, *xfile, *alertfile, *trafffile, *config, *log_pkt_file,
*log_pair; // files

// ----- CI weights ----- //
#define HO_ATTACK_INIT_CI 2000 // half-open attack from initial flow eval
#define HO_ATK_PER_SYN 501 // half-open attack per SYN, final flow eval
#define PORT_SCAN_CI 666 // per short-term port scan detected
#define PORT_SCAN_LT_CI 999 // per long-term port scan detected
#define PORT_SCAN_MAX 8 // max number of ports on all host 1st probed in
30s
#define PORT_SCAN_LT_MAX 16 // max number of ports on all host 1st probed long
term
#define PORT_SCAN2_CI 10 // per flow with no C or S determined
#define HI_HI_CI 50 // per high-port to high-port connection
#define LO_HI_CI 500 // per low-port to high-port connection
#define LO_LO_CI 100 // per low-port to low-port connection
#define UNKNOWN_CI 3 // per low-port to low-port connection
#define HOST_SCAN_CI 3000 // per address scan detected

#undef CHECK_INDEX // check HASH INDICES for out-of-range
#undef TEST // check for URG PTR != 0, flag-exception errors
#define FLOW_DEAD 320 // inactive time -> flow finished must be > 300 for
'persistent' http
#define LOOSE_PERIOD 900 // time in seconds for 'loose' classification of flows that
start
#define LINES_PER_SCREEN 40 // 1.6 x rough number of lines on Traffic and CI
Alerts web screens
#define SHORT_UDP_MAX 2 // max size for UDP data fields in a "short UDP"
#define UDP_PORT_OFFSET 2048 // added to udp ports before using port no. as offset
in port_mask[j]
#define PORT_MASK_SIZE 2058 // to dimension port_mask[] should be 4 larger
#define LOW_PT_MAX 1024 // a "low" port is less than this

#define SLOTS 131073 // no. flows in data table > 2**SHIFT+1 8193 16385 32769 65537
131073 262145
#define SHIFT 17 // size of shifts to make index. Max = 13 14 15 16
17 18
#define MASK 0x1ffff // mask all but Max-SHIFT right-most bits x1fff x3fff x7fff
xffff x1ffff x3ffff
#define RANGE 15 // search range for empty slot
struct flow_db {
    unsigned long ip[2]; // 0 - ip address - lowest
    unsigned short pt[2]; // tcp or udp ports

```

```

                                LANcope Code
unsigned short pt_min ; // client minimum port
unsigned short pt_max ; // client maximum port
unsigned long root ;
unsigned long down ;
unsigned long up ;
unsigned long start ;
unsigned long last ;
unsigned long state ; // FLOWTYPE =0,2 or for 4-TCP, 1-UDP classified =
0x10
unsigned short service ; // well-known port number of service, even if on a
different port
unsigned short scans ; // max number ports for ip0 pair
unsigned long bytes[2] ;
unsigned long pkts[2] ;
unsigned long flgs[2] ;
unsigned short binary[2] ;
unsigned short bin_norm[2] ;
unsigned char flag[2][7] ; // 0 bad, 1 reset, 2 urgent, 3 syn, 4 syn-ack, 5
fin&!ack, 6 fin&ack
unsigned char flag_norm[2] ; // urg ptr
} flow[SLOTS] ;
// elements in flow[ ].flag[j][ FLAG ]
#define BAD 0
#define RST 1
#define URG 2
#define SYN 3
#define S_A 4 // SYN-ACK
#define ATK_CTR // attack counter
// bits in flow[ ].state // 1 - udp, 2 - ip0 first, 4 - ip1 first
#define UDP_FLOW 0x01 // x0, x2, x4 are TCP stages
#define LOOSE 0x10 // loose matching for startup an split-path
#define ip0_FIRST 0x20 // ip0 sent first packet
#define ip1_FIRST 0x40 // ip1 sent first packet
#define NOT_FIRST_PKT 0x60 // first packet when neither ip0_FIRST nor ip1_FIRST is
set
#define FIRST_IN_FLO 0x60 // mask to test for "not loose and this is first pkt of
flow"
#define NO_SYN 0x80 // first TCP packet seen was not a SYN
#define CLASSIFIED 0x100 // clasified, but continue to watch
#define ATTACK 0x200 // do not continue checking (attack noted)
#define PROBE 0x400 // probe
#define ATK_PROBE 0x600 // ATTACK or PROBE
#define ATTACK_CHK 0x800 // log all packets after WATCH or ATTACK is set
#define FTP_SER_0 0x1000 // FTP_EST = FTP_OLD | FTP_PASS
#define FTP_SER_1 0x2000 // passive FTP, server is ip1 data is on a hi-hi
connection
#define FTP_ANY 0x3000 // any type FTP if true
#define HI_HI 0x4000 // both ports > 1023
#define WATCH_FLOW 0x8000 // marks flow so packets and flow is logged

#define SCAN_SLOTS 4097 // ip-pair data to detect scans, 2^n + 1 1025 2049
4097 8193
#define SCAN_SHIFT 12 // size of shifts to make index. Max =n 10 11
12 13
#define SCAN_MASK 0xffff //mask all but Max-SHIFT right-most bits x3ff x7ff
xffff x1fff
#define SCAN_RANGE 25 // search range for empty slot

#define SCAN_MAX 4 // ip-pair flow[i] elements limit for same IP, different
ports

struct ip_pair {
    unsigned long ip0 ; //ip address - source

```

```

                                LANcope Code
unsigned long ip1 ;                //ip address - target
unsigned long root ;
unsigned long down ;
unsigned long up;
unsigned long start ;
unsigned long last ;
unsigned long concern ;
unsigned short n_ports ;
unsigned short n_hits ;
unsigned char type[16] ; // values below
unsigned char walk[16] ; // distance of port walk
unsigned short port[16] ;
} scans[SCAN_SLOTS] ;

#define UDP_PROBE      1 // values for scans[i].type[ VALUE ]
#define TCP_PROBE      2
#define SHORT_UDP_SCAN 3
#define BOOMERANG      4
#define PING_SCAN      5
#define ICMP_TO        6
#define TCP_TO         7
#define UDP_TO         8
#define BAD_PKT_TRACE  9
#define TCP_PORT_SCAN 10
#define TCP_ADDR_SCAN 11
#define HALF_OPEN      12

unsigned long scin[16], scans_pr_cut, scans_cut ; // distribution of scans[].concern
values
unsigned long scan_pair(unsigned long ip0,unsigned long ip1,unsigned char
type,unsigned short port);

#define HOST_SLOTS 65537 // number Host slots                2^N + 1    16385 32769
65537 131073 262145
#define HOST_LIMIT 20000 // point to start dropping old outside host records with
CI=0 ;
#define HOST_SHIFT 16 // size of shifts to make index. Max =n    14    15
16    17    18
#define HOST_MASK 0xffff //mask all but Max-SHIFT right-most bits    x3fff x7fff
xffff x1ffff x3ffff
#define HOST_RANGE 25 // search range for empty slot
#define HOST_MAX 4 // ip-pair flow limit HOSTS
struct host_db {
    unsigned long ip ;                //ip address
    unsigned long root ;
    unsigned long down ;
    unsigned long up;
    unsigned long start ;
    unsigned long last ;
    unsigned long udp_bytes ; // multimedia bytes
    unsigned long bytes_in ; // for web_alert period
    unsigned long bytes_in_pp ; // Bytes over 5 min (wai)
    unsigned long bytes_in_mx ; // max all day
    unsigned long pkts_in ;
    unsigned long flgs_in ;
    unsigned long bytes_ot ; // for web_alert period
    unsigned long bytes_ot_pp ; // Bytes over 5 min (wai)
    unsigned long bytes_ot_mx ; // max all day
    unsigned long pkts_ot ;
    unsigned long flgs_ot ;
    unsigned long port_smin ; // 6 -> Server ports (0-1023)
    unsigned long port_smax ;
    unsigned long port_cmin ; // 7 -> Client of ports ( 0-1023)

```



```

                                LANcope Code
unsigned long port_cmax ;
unsigned long server      ; // 32 common server ports - provided
unsigned long client      ; // 32 common server ports - used
unsigned long s_profile   ; // 32 common server ports - provided
unsigned long c_profile   ; // 32 common server ports - used
unsigned short s_list[10] ; // list of uncommon servers
unsigned short c_list[10] ; // list of uncommon clients
unsigned long s_flows     ; // Server flows
unsigned long c_flows     ; // Client flows
unsigned long u_flows     ; // Unknown (not CS) flows
unsigned long resets      ; // TCP Resets
unsigned long rejects     ; // icmp 'port unavailable'
unsigned long no_con_t    ; // tcp, no response
unsigned long dns_flows   ; // DNS flows
unsigned long mm_s ; // multimedia server
unsigned long mm_c ; // multimedia client
unsigned long mm_p ; // multimedia peer
unsigned long pt_scans ; // no answer flows , e.g. scanning
unsigned long host_scan[5] ; // used to detect host scans
unsigned char scan_cntr[4] ; // used to count bits port scans H32
is 0, H128 1, P_ST 2, P_LT 3
unsigned long port_scan[4] ; // used to detect port scans
unsigned long bad_pkts ; // SYN-ACK, and any other than stadard 7
unsigned long bad_flow ; // Not Server < 1024, Client > 1024
unsigned long pings ; // pings
unsigned long traces ; // traces
unsigned long alerts ; // bit map of alert condition
unsigned long alarm_t ; // last time an alarm was set
unsigned long concern ; // accumulated CI
} host[ HOST_SLOTS ] ;

#define LOCAL_NETS 20 // maximum number of local subnets
// #define IRC 0x40000 // bits in host[].server or client above those read
// in from "lancope_config"

#define LOCAL_HOST 0x1 // bits in host[].alerts
#define PING_ALERT 0x2
#define TRACE_ALERT 0x4
#define REJECT_ALERT 0x8
#define PKT_ALERT 0x10
#define PT_SCAN_ALERT 0x20 // from flows exceding SCAN_MAX
#define PORT_SCAN2 0x40 // from bits in host.[h].port_scan[0]
#define HI_HI_CS 0x80
#define LO_HI_CS 0x100
#define LO_LO_CS 0x200
#define SHORT_UDP 0x400 // UDP packet with < 4 bytes data
#define IP_SCAN 0x800 // accessed too many different IP addresses
#define HO_ATTACK 0x1000 // Half-open attack
#define LT_PT_SCAN 0x2000 // Long-Term port scan
#define TRAF_ALARM 0x4000 // TRAFFIC bytes in + out over 15 min too high. Email
alerts sent and Web Bulletin
#define ALARM_1 0x8000 // alarm-1 talked with a suspicious host, flows & full
host info logged
#define ALARM_2 0x10000 // alarm-2 is a definite problem. Email alerts sent
and Web Bulletin
#define NO_ALARM 0x20000 // exempt from alarms
#define WATCH_HOST 0x40000 // log packets and flows
#define NO_CS_SET 0x80000 // C-S not determined (long-duration flow?)

#define ALARM_12 0x18000 // for host[i].alarms, 1 and/or 2
#define ALARM_12W 0x58000 // alarm-1 or alarm-2 or watch-host - log this guy's
packets and flows
char alert_name[32][25] =

```



```

                                LANcope Code
pthread_mutex_t mp_bs          = PTHREAD_MUTEX_INITIALIZER ; // stops bs[].t from
being written while read
pthread_t        thread_num[100] ;
volatile long    np, running = 1 ;
char             monitor_start[64] ; // capture start time

long find_slot( unsigned long ip0, unsigned long ip1, long port0, long port1); //
find slot in flow[ ]
unsigned long find_host( unsigned long ip, unsigned int make) ;
unsigned long dots_int( char *p ) ; // dotted-decimal (ascii) to integer
unsigned long s2i( unsigned char bb[4]) ; // 4 bytes -> 32 bit integer, Internet
order, msb on left [0]
unsigned long b2i( unsigned char bb[4]) ; // 4 bytes -> 32 bit integer,
intel-86order, msb on right [3]
void print_host(FILE *xfile, unsigned long i, unsigned long x) ;
void usage( void ) ;
int start_tcpdump( void ) ; // returns '0' if ok
void kill_tcpdump( void ) ;
void process_pkts( void ) ; // run as threads
void class_flow( void ) ;
void web_alerts( void ) ;
void record_probe( unsigned long hs, unsigned long des_addr, unsigned short des_port
) ;

void services( unsigned int x ) ;
void read_thresholds( void ) ;
int read_profiles( void ) ;
int save_profiles( void ) ;
void suicide( int yesterday) ; // saves logs and restarts this program (or newer
version)
void userhandler(int) ; // SIGTERM handler (control-c response)
#ifdef CHECK_INDEX
    unsigned long host_hash( unsigned long ip) ;
#endif

unsigned char snp_hdr[40], snp_buf[40], lan_buf[40], ip_buf[3000], *tcp_buf ;
//buffers
unsigned char ct[80], rt[80], as[20] ;
unsigned int   n_host = 1, n_pr_search, n_scans, slots_cut, slots_pr_cut ;

// FILE *tf ; //DeBuG    unsigned long temp[128] ;

unsigned long  i_src, i_des, hs_ip[128] ;

int ip_options_0 = 20, ip_options_1, data_0, data_1, restart_hour = 6 ; // gmt
long n_miss, n_max, n_flow, n_flow_log, t_read ;
unsigned char transport, scan_max ;
unsigned int  des_addr, src_addr, src_port, des_port, ah, tcp_all ;
unsigned short err_limit = 40, n_restart ;
unsigned long  flag_alr[256], flag_cnt[256], flags, n_icmp, n_tcp, n_udp, n_full,
port ;
unsigned long  snp_rec_max , host_cut ; // 24 + snaplen option used for Snoop

int f_dotdec, f_all, f_encrypt, f_file, f_demo, f_splitpath, f_loose, f_verbose,
f_noread ; // flags
int n_active, n_active_max ; // used by class_flow()
int n_lost ; // flows lost due to no slot
int lan_hdr, both_hdr, snp_len, snoop ;// lan_hr = 14 Ethernet, 21 FDDI
unsigned long non_ip, ip_not4, short_ip, ip_len[16], not_tui ; // for cleaning

```

```

int main(int argc, char * argv[ ]) // ===== MAIN =====
{

```

```

                                LANcope Code
    struct tm      *s_time, *cap_time ;
    clock_t      t_1, t_2 ; // t_1 = time in 1/60 s ,      clock_t is unsigned long
    time_t      t_now, snoop_t ; // time in sec since 1-1-1970, unsigned long
    struct timespec ts ; // ts.tv_sec and ts.tv_nsec
    char *inp, logflo[130], logpkt[130], logscan[130], *opx, app[130], alt[130] ;//
inp:infile
    unsigned long i, j, k, h, n, index, index0 ; // index to data table
    unsigned long pkt_len, inclu_len, rec_len, cu_drop ; // pkt record
header
    unsigned long t_start, t_last ; /* time */
    unsigned char x, y ;
    unsigned long save_old, n_list, n_err, m ; // used while reading
// ----- FOR HOST STATISTICS -----
    int ntf, nprof, hdr_needed ;
    unsigned short port_ck = 0 ; // TCP or UDP port numbers
    unsigned char c, flg , run_flags[120];
// Unique to Select.c
    unsigned long ipv[40], n_ips, v, snap_len, cap_len ;
    char ips[200], *spl, *sp2, *cap_prog, as0[200], as1[200], cmd[ 100 ],
filebase[100] ;
    unsigned long ip0, ip1, n_slot, no_header ;
    void (*handlerptr)(int); // for SIGTERM handle

    printf("\nProgram ID: %s\n ptr host[1] : %u, %u\n" , progid, (size_t)
&host[2],
(size_t) &host[2].ip ) ;
    if ( argc < 3 ) { // Snoop Pkt Size optional
        printf(" *** Not Enough Auguments\n"); usage() ;
    }

    handlerptr = signal(SIGTERM, userhandler);
    if (handlerptr == SIG_ERR) printf("Can't assign signal handler.\n");

    inp = argv[1]; //input file name

//    if(strstr(inp,"/")) {
//        printf("\n ### INPUT FILE MUST BE IN THE DEFAULT DIRECTORY
###\n\n");
//        usage() ;
//    }

    if(argc > 2) strcpy(logflo,argv[2]) ;

//    tf = fopen("host_scan_data.txt","w") ; // temp - Print Host Scan Data //
DeBuG

    t_now = time( NULL ) ; // present time in seconds

    if(logflo[0] == '-') {
        unsigned long day, hour ;
        day = (t_now / 86400) % 30 ;
        hour = (t_now / 3600) % 24 ;
        if( hour >= restart_hour) day = (day + 1) % 30 ;
        sprintf(logflo, "log-flows-%u.txt" , day ) ; // use same files
if restart in same day
        sprintf(logpkt, "log-pkts-%u.snp" , day ) ;
//        struct tm *w_time ;
//        w_time = localtime( & t_now ) ; // w_time points to 'tm' structure
//        strftime(logflo, 16, "%y%m%d%H", w_time) ; // t_table is formatted into
string ts

    }
//    strcpy( filebase, logflo ) ; // save for restart

```

LANcope Code

```
//      strcpy(logpkt, logflo) ;
//      strcat(logpkt, "log.snp" ) ;
//      strcpy(logscan, logflo) ;
//      strcat(logscan, "-scans.snp" ) ;
//      strcat(logflo, "-flow.txt" ) ;

printf("Selected flows listed in File: '%s', packets in '%s'\n", logflo, logpkt) ;

#ifdef CHECK_INDEX
    printf("    --- INDEX CHECKING IS TURNED ON ---  \n");
#endif

    if(argc > 3) { // --- set flags
        strcpy(run_flags,argv[3]) ;
        printf(" Flags: '%s'", run_flags );
        //      if(strstr(run_flags,"d")) {f_dotdec = 1; printf(" dotdec, " ) ;
    } // write IP addrs in dotted decimal
        if(strstr(run_flags,"a")) {f_all = 1; printf(" all flows,") ; }
    // fprint all flows that terminate
        if(strstr(run_flags,"e")) {f_encrypt = 1; printf(" encrypt, " ) ; }
    // encrypt local net names
        if(strstr(run_flags,"f")) {f_file = 1; printf(" file in, " ) ; }
    // take t_pace from file
        if(strstr(run_flags,"o")) {f_demo = 1; printf(" demo, " ) ; }
    // demo, list all hosts
        if(strstr(run_flags,"n")) {f_noread =1; printf(" no profiles, ");}
    // skip old profiles
        if(strstr(run_flags,"s")) {f_splitpath=1; printf(" split_path, ");}
    // some packets missing
        if(strstr(run_flags,"v")) {f_verbose =1; printf(" verbose, " ) ; }
    // verbose
        if(strstr(run_flags,"vv")) {f_verbose =2; printf("-very" ) ; } //
very verbose
        if(strstr(run_flags,"vvv")){f_verbose =3; printf("-very" ) ; } //
very verbose
        if(strstr(run_flags,"vvvv")){f_verbose=4; printf("-very" ) ; } //
very verbose
        printf("\n");
    }
    f_loose = 1 ; // after t_run > LOOSE_PERIOD, f_loose = f_splitpath

// ----- File opening for input from TCPDUMP or real file----- //
    if(f_file == 0 ) {
        if( start_tcpdump() ) {
            printf(" ### eth1 OR tcpdump CAN NOT BE STARTED -
TERMINATING ###\n\n");
            usage() ;
        }
    }
    else {
        if((infile = fopen (inp,"rb"))==NULL) { // OPEN INPUT FILE//
            printf("Input File %s Can Not Be Read\n", inp) ;
            usage() ;
        }
        if((config = fopen ("lancope_config.txt","rb"))==NULL) { // OPEN INPUT
FILE
            printf("Input File 'lancope_config.txt' Can Not Be Read\n", inp) ;
            usage();
        }
        while(1) { // read configuration parameters - port numbers,mask, and names
            unsigned int i , j ;
            if( EOF == fscanff(config," %u %u", &i, &j) ) break ; // read
            Page 8
        }
    }
}
```

LANcope Code

values of i, j

```

        if(( i >= 9000 ) || ( j > 31 )) break ;
        if( EOF == fscanf(config," %s", &port_name[j] ) ) break ; // read
port name
        if( i <= ( 2 * UDP_PORT_OFFSET )) {
                port_mask[ i ] = 1 << j ;
                pn_max = j + 1 ;
        }
        port_mask[ 2 * UDP_PORT_OFFSET + 1 ] = 1 << pn_max ;
strcpy(port_name[pn_max], "MMedia"); pn_max ++;
        port_mask[ 2 * UDP_PORT_OFFSET + 2 ] = 1 << pn_max ;
strcpy(port_name[pn_max], "M'cast"); pn_max ++;
        port_mask[ 2 * UDP_PORT_OFFSET + 3 ] = 1 << pn_max ;
strcpy(port_name[pn_max], "B'cast"); pn_max ++;
        port_mask[ 2 * UDP_PORT_OFFSET + 4 ] = 1 << pn_max ;
strcpy(port_name[pn_max], "Odd:") ; pn_max ++;

        ln_max = 0 ;
        while(1) { // ### read configuration parameters - local sub-nets ###
                if( EOF == fscanf(config," %s %s", pbuf_1, pbuf_2) || (atoi(pbuf_1)
> 256)) break ;
                local_net[ ln_max ] = dots_int( pbuf_1 ) ; // dotted decimal to
integer
                local_mask[ ln_max ] = dots_int( pbuf_2 ) ;
                if( f_encrypt ) {
                        unsigned int a ;
                        a = local_net[ ln_max ] ;
                        if( ! (local_mask[ ln_max ] & 0x0f00 )) local_mask[ ln_max ]
&= 0xffff0000 ; //for B-C class
                        local_net[ ln_max ] ^= (((a>>4)&0x0f0f0000) ^
(a<<4)&0x0000f000) ; //encrypt routine 'c'
                        a = local_net[ ln_max ] ;
                        printf("Encrypted Local Net: %u.%u.%u.%u, \t", a>>24,
(a>>16) & 0xff, (a>>8) & 0xff, a & 0xff ) ;
                }
                if( (++ln_max) >= LOCAL_NETS ) break ;
                printf("Local Net: %15s, Net Mask: %15s\n", pbuf_1, pbuf_2 ) ;
        }
        fclose( config) ;

        if((log_pair = fopen("log_pair.txt","ab"))==NULL) {
                printf("\nLog-Packets File 'log_pair.txt' Can Not Be Opened for Append\n\n")
;
        }
        usage() ;
}

```

```

pthread_mutex_lock( &mp_hosts) ; // ### lock hosts[]
        read_thresholds() ; // initial values for web_alert2, web_traf2,
restart_hour, profile ;
pthread_mutex_unlock( &mp_hosts) ; // ### unlock hosts[] - no_alarms and
watch_list

```

```

        if( ( ! f_noread) && ( profile >> 0 ) ) read_profiles() ; // ### read
profiles ###
        printf("\n Waiting for IP Data\n") ;

// --- read SNOOP FILE header into snp_buf[ ]
        no_header = 1 ;
        while( no_header ) {
                no_header = 0 ;
                n = fread( (void *) snp_hdr, 4, 4, infile) ;

```

LANcope Code

```

if( n<4) {
    printf("Could not read file header from %s\n\n", inp) ;
    no_header = 1 ;
}
else {
    if(
(snp_hdr[0]=='s')&&(snp_hdr[1]=='n')&&(snp_hdr[5]==0)&&(snp_hdr[11]==2) ){ // snoop
        snp_hdr[7] = 0x00 ;
        printf("%s %s Version %u, Format %u (4=Ethernet,
8=FDDI)\n", snp_hdr, &snp_hdr[6], \
(int) snp_hdr[11], (int) snp_hdr[15]);

        if( snp_hdr[6] == 'c' ) f_encrypt = 1 ; // encrypt
        if( snp_hdr[15] == 4 ) lan_hdr = 14 ; // Ethernet
        else {
            if(snp_hdr[15] == 8 ) lan_hdr = 21 ; // FDDI
            else {
                printf("\nFile is not 'snoop' of Ethernet or FDDI.
Type = %d\n\n", (int) snp_hdr[15] ) ;
                no_header = 1 ;
            }
            both_hdr = lan_hdr + 24 ;

            if(
(snp_hdr[0]!='s')||(snp_hdr[1]!='n')||(snp_hdr[5]!=0)||(snp_hdr[11]!=2) ){
                printf("\nFile is not 'snoop'
version '2' \n\n") ;
                no_header = 1 ;
            }
            cap_prog = "snoop" ;
            // Read 1st Snoop Record Header to get starting time
            n = fread( (void *) snp_buf, 4, 6, infile) ; //
read 1st snoop RECORD header into pf[ ]
            if( n < 6) { printf("\nEOF BEFORE FIRST RECORD\n\n")
;usage() ; }

            //      pkt_len  = s2i( &snp_buf[ 0] ) ;
            //      inclu_len = s2i( &snp_buf[ 4] ) ; // captured
length
            rec_len  = s2i( &snp_buf[8]) ; // SNOOP record
length (24 + captured length)
            //      cu_drop  = s2i( &snp_buf[12] ) ; // not used
            t_read = snoop_t = s2i( &snp_buf[16] ) ; //
absolute capture time in seconds
            snoop = 1 ; // cap program was snoop

        } else {
            // tcpdump
            if( snp_hdr[3] < 0xa1 ){
                printf("\nFile is not 'snoop' version '2' or
a TCPDUMP -w file\n\n") ;
                printf("1st 4 bytes are: %x,%x,%x,%x\n",
snp_hdr[0],snp_hdr[1],snp_hdr[2],snp_hdr[3]);
                usage() ;
            }
            lan_hdr = 14 ; // Ethernet
            both_hdr = lan_hdr + 24 ;
            cap_prog = "tcpdump" ;
            snoop = 0 ; // not snoop

```

LANcope Code

```

n = fread( (void *) &snp_hdr[16], 4, 2, infile) ;
// get extra length of tcpdump file header
if( n < 2) {
    printf("\nEOF BEFORE FIRST RECORD\n\n") ;
    no_header = 1 ;
}
else {
    snap_len = snp_hdr[16] + 256 * snp_hdr[17] ;

    // Read 1st tcpdump Record Header to get starting
time
n = fread( (void *) snp_buf, 4, 6, infile) ;
// read 1st snoop RECORD header into pf[ ]
if( n < 6) {
    printf("\nEOF BEFORE FIRST
RECORD\n\n") ;
    no_header = 1 ;
}
else {
    rec_len = b2i( &snp_buf[8]) + 24 ;
    // tcpdump record length (24 + captured length)
    t_read = snoop_t = b2i(
&snp_buf[0] ) ; // absolute capture time in seconds
    printf(" tcpdump -s (raw) capture
file, snap_len = %u\n", snap_len ) ;
}
} // end tcpdump specific read
}

if( no_header ) {
    if( f_file ) usage() ;
    else {
        start_tcpdump() ;
        printf(" #### WILL TRY TO READ HEADER AGAIN ###
\n") ;
    }
    if( running != 1 ) goto wrapup ;
    sleep(1) ;
} // end - while( no_header)

snp_rec_max =250 ;

// printf("Run_flags: '%s', Snoop Record Max. Length: %u bytes\n", run_flags,
snp_rec_max ) ;

{
    struct stat file_info; // -----OPEN OUTPUT FILE log-flow-n.txt
and log-pkt

    if( stat( logflo, &file_info) != 0 ) { // file logflo does
not exists already
        if((log_flow = fopen (logflo,"wb"))==NULL) {
            printf("\nLog-Packets File %s Can Not Be Created\n\n",
logflo) ;
            usage() ;
        }
        hdr_needed = 1 ;
    }
    else { // file logflo
exists already

```



```

                                LANcope Code
                                if((log_flow = fopen (logflo,"ab"))==NULL) {
Append\n\n", logflo) ;                                printf("\nLog-Packets File %s Can Not Be Opened for
                                usage() ;
                                }
                                hdr_needed = 0 ;
                                }

                                if( stat( logpkt, &file_info) != 0 ) { // file logpkt does not
exists already                                if((log_pkt_file = fopen (logpkt,"wb"))==NULL) {
                                printf("\nLog-Packets File %s Can Not Be Created\n\n",
logpkt) ;                                usage() ;
                                }
                                fwrite( snp_hdr, sizeof(char), 24, log_pkt_file ) ; // copy
tcpdump file header into packet log file
                                }
                                else { // file logpkt
exists already                                if((log_pkt_file = fopen (logpkt,"ab"))==NULL) {
Append\n\n", logpkt) ;                                printf("\nLog-Packets File %s Can Not Be Opened for
                                usage() ;
                                }
                                }

                                }

                                t_now = t_1 = time(NULL) ; // puts present time (s) into t_now and
GLOBAL t_zero                                if( f_file) { t_zero = t_read ; } else { t_zero = t_now ; }
                                s_time = localtime(&t_now); // puts ascii data in struct( *captime),
makes s_time point to it                                strcpy( rt, asctime( s_time ) ) ; // rt has \n

                                cap_time = localtime( &snoop_t ) ;
                                strcpy( ct, asctime( cap_time ) ) ;
                                strcpy(monitor_start, "Monitoring Started: ") ;
                                strcat(monitor_start, ct ) ;
                                monitor_start[ 39 ] = ',' ; // chop off year and \n for web page title
                                monitor_start[ 40 ] = ',' ;
                                monitor_start[ 41 ] = 0 ;

                                fflush(stdout) ;
                                t_2 = clock() ;

                                printf("Data captured by %s to file %s on %s", cap_prog, inp, ct ) ; // ct
has \n                                printf("Program ID: '%s'.\nRun on %s. Output file: %s\n", progid, rt,
logflo);                                if( hdr_needed ) {
fprintf(log_flow, "Data captured by %s to file %s on %s", cap_prog, inp, ct ) ; //
ct has \n                                fprintf(log_flow, "Program ID: '%s'.\nRun on %s. Output file: %s\n", progid, rt,
logflo);                                fprintf(log_flow,"prot\tip0\tip1\tport0\tport1\tservice\tstart\tlast\tbytes0\tpkts0\
tflags0\t");
                                fprintf(log_flow,
                                "p-min0\tp-max0\tbinary0\tBad0\tRST0\tURG0\tSYN0\tSYN-ACK0\tFIN0\tU-PTR0\t" );
                                fprintf(log_flow, "bytes1\tpkts1\tflags1\tp-min1\tp-max1\t");
                                fprintf(log_flow, "binary1\tBad1\tRST0\tURG1\tSYN1\tSYN-ACK1\tFIN1\tU-PTR1\n" );
                                }
                                // ##### START THREADS TO READ PACKETS and CLASSIFY FLOWS

```

LANcope Code

#####

```
pthread_create( &thread_num[1], NULL, (void *) &process_pkts, NULL ); //
### NEW THREADS
    if( f_file ) pthread_mutex_lock(
&mp_class_flow ); // block class_flow() until p_p releases
    pthread_create( &thread_num[2], NULL, (void *) &class_flow , NULL );
    pthread_create( &thread_num[3], NULL, (void *) &web_alerts , NULL ); //
ALERT TABLES FOR WEB
```

```
// ### Three threads run until userhandler() detects SIGTERM and sets 'running =
2' ###
```

```
pthread_join( thread_num[1], NULL ); // wait for completion - until
'running' -> 2
printf(" Thread-1 (process_pkts) joined, ");
running = 2 ;
if( f_file) pthread_mutex_unlock( &mp_class_flow );
pthread_join( thread_num[2], NULL );
printf(" Thread-2 ( class_flow ) joined, ");
// pthread_join( thread_num[3], NULL );
// printf(" Thread-3 ( web_alerts ) joined\n");
```

```
// ##### END OF THREADS #####
```

wrapup:

```
printf("\n*** Packet Data Source Ended, Flow Log: %s, Pkt Log:
%s\n\n", logflo, logpkt );
time(&t_now);
s_time = localtime(&t_now);

xfile = stdout ; // 1st time through
fprintf(xfile, " Flows found: %u, logged: %d, packets: %u, time-out:
%d \n",
                                n_flow, n_flow_log, np, FLOW_DEAD)
;
    fprintf(xfile, " TCP packets: %u, UDP packets: %u, ICMP packets:
%u\n", n_tcp, n_udp, n_icmp) ;
    fprintf(xfile, "\nIt took %u seconds to process, %u pkts, %u cap.
secs.\n", time(NULL) - t_1, np, t_run);
// xfile = log_flow ; // 2nd time through
//{
//    for( i = 0 ; i < 128 ; i++ ) { // DeBuG
//        fprintf(tf, "%u\t%u\t", i, temp[ i ] ) ;
//        if( hs_ip[ i ] == 0 ) fprintf(tf, "\n") ;
//        else {
//            register unsigned int a ;
//            a = hs_ip[ i ] ;
//            fprintf(tf, "%3u.%3u.%3u.%3u\n", a>>24, (a>>16) & 0xff,
(a>>8) & 0xff, a & 0xff) ;
//        }
//    }
//    printf(" Host Scan Data saved in file host_scan_data.txt\n");
//}
save_profiles() ;
```

```
for( i = 1 ; i < SCAN_SLOTS ; i++ ) { // ### WRITE SCAN-PAIRS ###
IDENTICAL TO CODE IN web_alerts()
    register unsigned int ip0, ip1, done;
    char as0[20], as1[20], as[30], as4[30], pr_str[500], x_str[50] ;
    if( scans[i].down) { // select pairs to fprint
        ip0 = scans[i].ip0 ;
```

```

                                LANcope Code
                                ip1 = scans[i].ip1 ;
                                sprintf( as0, "%3u.%3u.%3u.%3u", (ip0>>24) & 0xff, (ip0>>16) & 0xff, (ip0>>8)
& 0xff, ip0 & 0xff) ;
                                sprintf( as1, "%3u.%3u.%3u.%3u", (ip1>>24) & 0xff, (ip1>>16) & 0xff, (ip1>>8)
& 0xff, ip1 & 0xff) ;
                                for( j = 0 ; j < strlen(as0) ; j++ ) if( as0[j] == '
') as0[j] = '0' ; // target ip0
                                for( j = 0 ; j < strlen(as1) ; j++ ) if( as1[j] == '
') as1[j] = '0' ; // prober ip1

                                sprintf(pr_str, "%u\t%u\t%s\t%s\t%u\t%u\t", scans[i].last,
scans[i].start, as0, as1,
                                scans[i].n_hits, scans[i].n_ports );
                                for( j = 0 ; j < 16 ; j++ ) {
                                    x_str[0] = 0 ; done = 0 ;
                                    switch ( scans[i].type[j] ) {
                                        case 1: sprintf(x_str, "UDP_R-%u", scans[i].port[j]) ;break ; //
UDP_PROBE
                                        case 2: sprintf(x_str, "TCP_R-%u", scans[i].port[j]) ;break ; //
TCP_PROBE
                                        case 3: sprintf(x_str, "Short_UDP-%u" , scans[i].port[j]) ;break ; //
SHORT_UDP_SCAN
                                        case 4: sprintf(x_str, "Src=Des-%u", scans[i].port[j]) ;break ; //
BOOMERANG
                                        case 5: sprintf(x_str, "Ping") ;break ; //
PING_SCAN
                                        case 6: sprintf(x_str, "ICMP_TO" ) ;break ; //
ICMP_TO
                                        case 7: sprintf(x_str, "TCP_TO-%u", scans[i].port[j]) ;break ; //
TCP_TO
                                        case 8: sprintf(x_str, "UDP_TO-%u", scans[i].port[j]) ;break ; //
UDP_TO
                                        case 9: sprintf(x_str, "Bad_TCP-%u", scans[i].port[j]) ;break ; //
BAD_PKT_TRACE
                                        case 10: sprintf(x_str, "Multi_Pt-%u", scans[i].port[j]) ;break ; //
TCP_PORT_SCAN
                                        case 11: sprintf(x_str, "Addr_Scan-%u", scans[i].port[j]) ;break ; //
TCP_ADDR_SCAN
                                        case 12: sprintf(x_str, "HO_ATTACKn-%u", scans[i].port[j]) ;break ; //
HALF_OPEN
                                        default : done = 1 ;
                                    }
                                    if( done ) break ;
                                    strcat( pr_str, x_str ) ;
                                    if( scans[i].walk[j] > 0 ) {
                                        sprintf(x_str, "(%u) ", scans[i].walk[j] )
;
                                        strcat( pr_str, x_str) ;
                                    }
                                    else strcat(pr_str, " " ) ;
                                } // end j = 0, 1,2, ...
                                strcat(pr_str, "\n") ;
                                fprintf(log_pair, "%u\t%s", scans[i].concern, pr_str) ; // write to
log before deleting
                                }

                                n = 0 ;
                                for( i = 1 ; i < SLOTS ; i++ ) {
                                    if(flow[i].down) {
                                        n++ ;
                                    }
                                }
}

```

```

                                LANcope Code
printf("  Max. Search: %d, Max. Flows Active: %d, Still Going: %u\n", n_max,
n_active_max, n );
kill_tcpdump() ;

//      running = 2 ; // finish up - force all flows to terminate
// class_flow() ;
// web_alerts() ;

//      printf("  All Flows Terminated and Classified\n");
//      sprintf( cmd, "lc_restart %s %s &", argv[3], filebase ) ;
//      exit(0) ;
}      //      ++++++ END MAIN() ++++++

```

```

void process_pkts( ) //      ### THREAD #1 ###
{
    unsigned long i, j, k, h, index, index0 ;          // index to data
table
    unsigned long  pkt_len, inclu_len, rec_len, cu_drop ; // pkt record
header
    long m, c_sec, t_sec, t_us, t_offset=0, t_cf, t_start ; // t_offset + or -
    unsigned long ip0, ip1, n_slot, n_err, n,  h0, h1, hs, hd, bytes, bytes_hdr
;
    time_t t_now, t_check, t_pause = 3 ;

    t_now = time(NULL) ;
    z_sec = t_read ;      // snoop time stamp values
    c_sec = z_sec ;
    t_run = 1 ;           // seconds since capture run started, must be > 0
    t_start = t_cf = 0 ;
    non_ip = ip_not4 = short_ip = n_err = not_tui = 0 ;
    for( i = 0; i < 16; i++) ip_len[i] = 0 ; // no. IP frames with header
length i,  i >= 5

    //      32 16 8 4 2 1
    for( i = 1 ; i < 256 ; i++ ) { // x,x,URG,ACK ,PSH,RST,SYN,FIN
        if( ( i & 0x3f ) == 0x3f ) flag_alr[i] |= 0x10000 ; // Christmas
attack
        if( ( i & 3 ) == 3 ) flag_alr[i] |= 0x20000 ; // Syn Fin,
Jackel or nmap
        if( ( i & 0xc0 ) > 0 ) flag_alr[i] |= 0x40000 ; // Reserved
Flags
        if( ( i & 4 ) && ( i & 0x23)) flag_alr[i] |= 0x080000 ; // RST and
any but PSH, ACK
        if( (~i & 0x10) && ( i & 0x29)) flag_alr[i] |= 0x100000 ; // no ACK,
any flag but SYN or RESET
        if( ( i & 0x20) && ( i & 0xc7)) flag_alr[i] |= 0x200000 ; // UGR +
any except ACK or PSH
    }
    flag_alr[0] = 0x400000 ; // no flags
    np = 0 ;

    if( f_file ) {
        unsigned int cfi = CLASS_FLOW_INT ; // cfi = 30 s
        unsigned int wai = WEB_ALERT_INT ; // wfi = 900
        t_next_cf = *(&t_zero) + 0.5 * cfi ;
        t_next_cf = t_next_cf + cfi - (t_next_cf % cfi) ; // moves to
nearest even value
    }
}

```

```

                                LANcope Code
restart_here:  printf("# Thread process_pkts start (%d) at t: %u, np:
%u\n", n_restart++, t_run, np) ;

    while (running == 1) {      // ##### START LOOP TO READ PACKETS
#####
        long port0, port1, log_pkt ;
        if( np == 0 ) goto read_ip_buf ; // already read snoop header
// *** PKT TIME FROM SNOOP HEADER ****
        if( f_file) {
            t_sec = t_read + t_offset;
            if ( ((( t_sec - c_sec) > 360 ) || ( t_sec - c_sec) < -10 )
|| ( t_sec < z_sec ) ) {
                //      printf( "BAD TIME VALUE, np:%u, Chk. T = %d, This T
= %d s, %d us, Error = %u", \
                np, c_sec, t_sec, t_us, n_err );
                //      if( abs(c_sec - t_sec) > 120 ) { // clock jump
                //          printf(" - Time Jump > 120 s. PACKET
                //          goto read_next ;
                //      }
                //      else printf("\n");
                //      printf("np: %u, Old T Offset = %d, ", np, t_offset
                //      t_offset += c_sec - t_sec ;
                //      t_sec = c_sec ;
                //      printf( ", New T Offset = %d\n", t_offset, t_run )
                //      if ( n_err++ > 30 ) break ; // go to wrapup
            }
            c_sec = t_sec ;
            t_run = t_sec - z_sec + 1 ; // data from file
        } else {
            t_run = t_read - z_sec + 1 ; // real-time, z_sec is time of
first packet
        }
// ===== PROCESS PACKET
=====
        log_pkt = 0 ; // do not log packet unless this is set
pthread_mutex_lock( &mp_flows) ; // ### lock hosts[]
pthread_mutex_lock( &mp_hosts) ; // ### lock hosts[]
if( f_verbose == 3 ) { printf(" np:%u received at %u, ", np, t_run ) ;
fflush(stdout) ; }
        if( !( (lan_buf[lan_hdr - 2] == 8) && ( lan_buf[lan_hdr - 1] == 0) )
) { // not an IP packet
            non_ip++ ;
            goto read_next ;
        }
        if( ( ip_buf[0] & 0xf0 ) != 0x40 ) { //IP, but not version 4
            ip_not4++ ;
            goto read_next ;
        }

        if( ( n = (ip_buf[0]) & 0x0f ) != 5 ) ip_len[ n ] ++ ; //IP, but
with options

// -----IP actions -----
        m = 4*n ; // zero data, start i adjusted for length of IP header
        if(( m < 0 ) || (m > 32)) {
            n_err++ ;
            printf("Length-Error Packet, %u. Length = %d 4-byte
words.\n", np, n) ;
            log_pkt = 1 ;

```

```

//                                LANcope Code
//                                if( n_err > err_limit ) goto wrapup ;
//                                else
//                                    goto read_next;
//                                }
tcp_buf = &ip_buf[ m ] ; // ip header length m = 20 unless there
are IP options
//                                ip_options_1 = m ;

src_addr = s2i( &ip_buf[12] ) ;
des_addr = s2i( &ip_buf[16] ) ;
transport = (unsigned char) ip_buf[ 9 ] ;

hs = find_host( src_addr, 1 ) ; // create entry if none exists
hd = find_host( des_addr, 0 ) ; // find hd if entry exists

if(src_addr == des_addr) {
pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
scan_pair( src_addr, des_addr, BOOMERANG, 0 ) ; // type 8 ->
circle packet or "land" attack
pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
log_pkt = 1 ;
goto read_next;
}

bytes_hdr = (((unsigned int) ip_buf[2] << 8 ) | (unsigned int)
ip_buf[3]); //includes IP, TCP/UDP/ICMP hdrs
bytes = bytes_hdr -m - 8 ; // length of IP data (includes
App. Header) UDP, ICMP = 8 bytes
if(transport == 6) bytes += 8 - 4 * (tcp_buf[12] >> 4) ; //
adjust for longer TCP header

// Traffic Stats - IP Spoof Detect
{
    unsigned int traf = 0, s, d ;
    for ( n = 0 ; n < ln_max ; n++) {
        if( ! ( local_mask[ n ] & ( local_net[ n ] ^
src_addr ))) traf |= 1 ; // source is local
        if( ! ( local_mask[ n ] & ( local_net[ n ] ^
des_addr ))) traf |= 2 ; // destin is local
    }
    if( ! (0xf0000000 & (0xe0000000 ^ des_addr) ) ) traf |= 4 ;
// => 4 (outside) or 5 (local) mcast

    if( !(des_addr & 0xff000000) || (((des_addr & 0xff000000)
== 0xff000000 )
|| ((des_addr & 0x000000ff) == 0x000000ff ) traf
|= 8 ; // local broadcast => 9, if 8 then bad
    if( ! (0xff000000 & (0xff000000 ^ des_addr) ) ) traf |= 8 ;
// => 4 (outside) or 5 (local)
    if( ( src_addr & 0xff000000) == 0 ) {
        if ( !( traf & 10 ) ) traf |= 16 ; // bad if
dest is not local or local broadcast (traf = 8 or 2)
        else traf = 9 ; // set to local broadcast
    }
    switch( traf ) {
        unsigned int ips, ipd ;

        case 0 : // outside-outside traffic

            spoofs++ ;
            bytes_oo_cnt += ( (unsigned int) ip_buf[2] << 8 ) |
(unsigned int) ip_buf[3] ;

```

LANcope Code

```

        if(spoofs < 10 ) {
            if(! f_encrypt) { //encrypt routine 'c'
                printf(" SPOOF PACKET- Source
%3u.%3u.%3u.%3u, Dest. %3u.%3u.%3u.%3u  t: %u\n",
                    (src_addr>>24) & 0xff,
                    (src_addr>>16) & 0xff, (src_addr>>8) & 0xff, src_addr & 0xff,
                    (des_addr>>24) & 0xff,
                    (des_addr>>16) & 0xff, (des_addr>>8) & 0xff, des_addr & 0xff,t_run);
            } else {
                ips = src_addr ^
                (((src_addr>>4)&0x0f0f0000) ^ (src_addr<<4)&0x0000f000) ;
                ipd = des_addr ^
                (((des_addr>>4)&0x0f0f0000) ^ (des_addr<<4)&0x0000f000) ;
                printf(" SPOOF?- Source
%3u.%3u.%3u.%3u, Dest. %3u.%3u.%3u.%3u  t: %u\n",
                    (ips>>24) & 0xff, (ips>>16) &
                    0xff, (ips>>8) & 0xff, ips & 0xff ,
                    (ipd>>24) & 0xff, (ipd>>16) &
                    0xff, (ipd>>8) & 0xff, ipd & 0xff, t_run ) ;
            } // end - spoofs < 10
        }
        break ;
    case 1 : // inside-outside traffic 0001
        bytes_in_cnt += bytes_hdr ; // bytes including
headers
        break ;
    case 2 : // outside-inside traffic 0010
        bytes_out_cnt += bytes_hdr ;
        break ;
    case 3 : // inside-inside traffic 0011
        bytes_loc_cnt += bytes_hdr ;
        break ;
    case 4 : // outside multicast 0100
        bytes_mcn_cnt += bytes_hdr ;
        if( hs ){
            host[ hs ].server |= port_mask[ 2050
] ; // mcast_bit
        }
        goto read_next ;
        break ;
    case 5 : // inside broadcast 0101
        bytes_mco_cnt += bytes_hdr ;
        if( hs ) { // create entry if none exists
            host[ hs ].server |= port_mask[ 2050
] ;// mcast_bit
        }
        goto read_next ;
        break ;
    case 9: // inside broadcast to 0.0.0.0 1001
    case 11: // inside broadcast to x.x.x.255 1011
        bytes_bc_cnt += bytes_hdr ;
        if( hs ) { // create entry if none exists
            host[ hs ].server |= port_mask[ 2 *
UDP_PORT_OFFSET + 3 ] ;// bcast_bit
        }

```

```

                                LANcope Code
                                goto read_next ;
break ;

default :
    bytes_bad_cnt += bytes_hdr ; // outside to broadcast
1001
                                log_pkt = 1 ;
                                goto read_next ;
    } // End case (traf)
} // end traffic stats

// ===== CHECK FOR PATHOLOGICAL PACKETS =====(LINE
651)===== //

// TCP and UDP Flow numbers
if((transport == 6) || (transport == 17)) { // collect flow data
    src_port = ((unsigned long) tcp_buf[0] << 8) | ((unsigned long) tcp_buf[1]
);// src port
    des_port = ((unsigned long) tcp_buf[2] << 8) | ((unsigned long) tcp_buf[3]
);// des port

    if( hs ) {
        host[ hs ].bytes_ot_pp += bytes_hdr ; // bytes_ot_pp
is bytes out per period (0'ed every 5 min.)
        host[ hs ].pkts_ot ++ ;

        if ( (transport == 6 ) && (flag_alr[ tcp_buf[13]
])) { // bad-flags TCP
            host[ hs ].bad_pkts ++ ;
            log_pkt = 1 ;
            record_probe( hs, des_addr, des_port ) ;

            if( host[ hs ].bad_pkts < 1000 ) {
pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
                scan_pair( src_addr, des_addr,
BAD_PKT_TRACE, des_port) ;
pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
            }

            if( transport == 17) { // UDP
                host[ hs ].udp_bytes += bytes_hdr; // bytes_hdr
includes header bytes
                host[ hs ].bytes_ot += bytes_hdr ;

                if (bytes <= SHORT_UDP_MAX ) { // too short
                    host[ hs ].bad_pkts ++ ; //
too-short UDP
                    host[ hs ].alerts |= SHORT_UDP ; //
too-short UDP

                    log_pkt = 1 ;
                    record_probe( hs, des_addr, des_port ) ;
pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
                    scan_pair( src_addr, des_addr,
SHORT_UDP_SCAN, des_port) ;
pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
                }
            }
            else host[ hs ].bytes_ot += bytes ; // TCP, data bytes
only

            if(( ip_buf[8] < 2 ) && des_addr) { // TTL expiring, TCP,

```



```

                                LANcope Code
UDP, OR ICMP, ignore b'cast to 0.0.0.0
                                host[ hs ].traces ++ ;
                                host[ hs ].alerts |= TRACE_ALERT ; // ICMP timeouts
are ignored
                                log_pkt = 1 ;
                                record_probe( hs, des_addr, src_addr ) ;
pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
                                if (transport == 6) scan_pair( src_addr, des_addr,
TCP_TO, des_port) ;
                                if (transport == 17) scan_pair( src_addr, des_addr,
UDP_TO, des_port) ;
pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
                                }

// ===== END - LOOKING FOR PATHOLOGICAL PACKETS
===== //

    if( hd ) {
        host[ hd ].bytes_in_pp += bytes_hdr ; // bytes_in_pp is
bytes in per period (0'ed every 5 min.)
        host[ hd ].pkts_in ++ ;
        if( transport == 17) { // UDP
            host[ hd ].udp_bytes += bytes_hdr ; // total UDP, in
and out, includes header bytes
            host[ hd ].bytes_in += bytes_hdr ;
        }
        else host[ hd ].bytes_in += bytes ; // TCP
    }

    if ( src_addr < des_addr ) { // ip0 is the smaller IP addr
        ip0 = src_addr ; port0 = src_port ;
        ip1 = des_addr ; port1 = des_port ;
        h0 = hs ; h1 = hd ;
    } else {
        ip1 = src_addr ; port1 = src_port ;
        ip0 = des_addr ; port0 = des_port ;
        h0 = hd ; h1 = hs ;
    }

    if( (n_slot = find_slot(ip0, ip1, port0, port1)) == 0) { // #####
Find slot in Flow data structure

        printf(" *** Flow Data Full np: %u, Scan_max: %u,
ip: %u, pt: %u, ip1: %u, pt1: %u\n",
                                np,scan_max,ip0,port0,ip1,port1) ;
        goto read_next ;
    }

#ifdef CHECK_INDEX
    if(n_slot > SLOTS ) {
        printf("Bad n_slot: %u, np:%u, t_run: %u\n", n_slot,
np, t_run );
        fflush(stdout) ;
        break ;
    }
#endif

    if((host[hs].alerts & WATCH_HOST) || (host[hd].alerts &
WATCH_HOST)) {
        flow[n_slot].state |= WATCH_FLOW ; // LOG THIS FLOW
AND ALL PACKETS
    }
    if((scan_max > SCAN_MAX) && (scan_max> flow[n_slot].scans))
{ // == PORT SCAN DETECTION

```

```

                                LANcope Code
                                flow[n_slot].scans = scan_max ;
                                log_pkt = 1 ;
                                }
                                if( ! (flow[n_slot].state & NOT_FIRST_PKT) ) { // this is
FIRST PACKET
                                if(( host[ hs ].alerts | host[ hd ].alerts) &
ALARM_12W ){
                                flow[n_slot].state |= WATCH_FLOW ; // log
all flows and pkts
                                }
                                if( flow[n_slot].state & LOOSE == 0 ){ // not LOOSE
and FIRST PACKET
                                if ( src_addr < des_addr ) {
                                flow[n_slot].state |= ip0_FIRST ;
                                flow[n_slot].service =
//
flow[n_slot].pt[1] ;
                                }
                                else {
                                flow[n_slot].state |= ip1_FIRST ;
                                flow[n_slot].service =
//
flow[n_slot].pt[2] ;
                                }
                                if( (transport == 6) && ( tcp_buf[13] !=
0x02 ) && (! f_loose )) { // not SYN, 1st packet not seen
                                if(( port0 != 25) && (port1 != 25))
flow[n_slot].state |= NO_SYN ; // do not set for Telnet
                                } // end - no SYN
                                } // not LOOSE
                                } // end - 1st packet in flow
                                } // end TCP or UDP
                                switch( transport ) // ACTION FOR DIFFERENT TRANSPORT PROTOCOLS
                                {
                                case 6 : // *** TCP ***
                                n_tcp++ ;
                                flags = (unsigned int) tcp_buf[13] | flag_alr[ tcp_buf[13] ] ; //
look up flag combinations, set bits 0,1,2,3
                                ah = (tcp_buf[12] >> 2) & 0x3c ; // tcp_buf[ah] == 1st application
header byte ;
                                if( ip0 == src_addr) {
                                flow[n_slot].pkts[0]++ ;
                                flow[n_slot].bytes[0] += bytes ; // does not include IP hdr
                                flow[n_slot].flgs[0] |= flags ;
                                if( (rec_len - both_hdr - m - 20) >= 4) { // app.header
>= 4 bytes long
                                if( flow[n_slot].bin_norm[0] < 0xffff )
flow[n_slot].bin_norm[0] += 1 ;
                                else {
                                flow[n_slot].bin_norm[0] = 0xcfff ;
                                flow[n_slot].binary[0] =
(flow[n_slot].binary[0] >> 1) + ( flow[n_slot].binary[0] >> 2 ) ; // 3/16
                                }
                                flow[n_slot].binary[0] +=
(tcp_buf[ah]>>7)+(tcp_buf[ah+1]>>7)+(tcp_buf[ah+2]>>7)+(tcp_buf[ah+3]>>7);

```

LANcope Code

```

    }
    if( flow[n_slot].flag_norm[0] < 0xffff )
flow[n_slot].flag_norm[0] += 1 ; // normalize if needed
    else {
        flow[n_slot].flag_norm[0] = 0xcf ;
        flow[n_slot].flag[0][0] = (flow[n_slot].flag[0][0]
>> 1) + ( flow[n_slot].flag[0][0] >> 2 )
        + (flow[n_slot].flag[0][0] & 1 ) ; // keep >
0 if ever > 0
        flow[n_slot].flag[0][1] = (flow[n_slot].flag[0][1]
>> 1) + ( flow[n_slot].flag[0][1] >> 2 )
        + (flow[n_slot].flag[0][1] & 1 ) ;
        flow[n_slot].flag[0][2] = (flow[n_slot].flag[0][2]
>> 1) + ( flow[n_slot].flag[0][2] >> 2 )
        + (flow[n_slot].flag[0][2] & 1 ) ;
        flow[n_slot].flag[0][3] = (flow[n_slot].flag[0][3]
>> 1) + ( flow[n_slot].flag[0][3] >> 2 )
        + (flow[n_slot].flag[0][3] & 1 ) ;
        flow[n_slot].flag[0][4] = (flow[n_slot].flag[0][4]
>> 1) + ( flow[n_slot].flag[0][4] >> 2 )
        + (flow[n_slot].flag[0][4] & 1 ) ;
        flow[n_slot].flag[0][5] = (flow[n_slot].flag[0][5]
>> 1) + ( flow[n_slot].flag[0][5] >> 2 )
        + (flow[n_slot].flag[0][5] & 1 ) ;
    }
    // update flag counters when ip0 is source
    if( flags & 0xffffffc0 ) {
        flow[n_slot].flag[0][0] ++ ; // flags >> 0x3f//
SYN-FIN et al
    }
    flow[n_slot].flag[0][1] += (flags >> 2) & 0x01 ; // RESET
    flow[n_slot].flag[0][2] += (flags >> 5) & 0x01 ; // URGENT
    flow[n_slot].flag[0][3] += ((~flags >> 4) & (flags >> 1) &
0x01) ; // not-ACK & SYN
    flow[n_slot].flag[0][4] += (( flags >> 4) & (flags >> 1) &
0x01) ; // ACK & SYN
    flow[n_slot].flag[0][5] += (( flags >> 4) & flags &
0x01) ; // ACK & FIN
    flow[n_slot].flag[0][6] |= (tcp_buf[18] | tcp_buf[19]) ; //
URG pointer
    }
    else
    { // ip1 == src_adr
        flow[n_slot].pkts[1]++ ; // [1] indicates ip[1] sent
        flow[n_slot].bytes[1] += bytes ;// does not include IP hdr
        flow[n_slot].flgs[1] |= flags ;

        if( (rec_len - both_hdr - m - ah) >= 4) {
            if( flow[n_slot].bin_norm[1] < 0xffff )
flow[n_slot].bin_norm[1] += 1 ;
            else {
                flow[n_slot].bin_norm[1] = ( unsigned char)
0xcf ;
                flow[n_slot].binary[1] =
(flow[n_slot].binary[1] >> 1) + ( flow[n_slot].binary[1] >> 2 ) ; // 3/16
            }
            flow[n_slot].binary[1] +=
(tcp_buf[ah]>>7)+(tcp_buf[ah+1]>>7)+(tcp_buf[ah+2]>>7)+(tcp_buf[ah+3]>>7); //add 0-4
        }

        if( flow[n_slot].flag_norm[1] < 0xffff )

```

```

LANcope Code
flow[n_slot].flag_norm[1] += 1 ; // normalize if needed
else {
    flow[n_slot].flag_norm[1] = 0xcf ;
    flow[n_slot].flag[1][0] = (flow[n_slot].flag[1][0]
>> 1) + ( flow[n_slot].flag[1][0] >> 2 )
    + (flow[n_slot].flag[1][0] & 1 ) ; // 3/4
    flow[n_slot].flag[1][1] = (flow[n_slot].flag[1][1]
>> 1) + ( flow[n_slot].flag[1][1] >> 2 )
    + (flow[n_slot].flag[1][1] & 1 ) ;
    flow[n_slot].flag[1][2] = (flow[n_slot].flag[1][2]
>> 1) + ( flow[n_slot].flag[1][2] >> 2 )
    + (flow[n_slot].flag[1][2] & 1 ) ;
    flow[n_slot].flag[1][3] = (flow[n_slot].flag[1][3]
>> 1) + ( flow[n_slot].flag[1][3] >> 2 )
    + (flow[n_slot].flag[1][3] & 1 ) ;
    flow[n_slot].flag[1][4] = (flow[n_slot].flag[1][4]
>> 1) + ( flow[n_slot].flag[1][4] >> 2 )
    + (flow[n_slot].flag[1][4] & 1 ) ;
    flow[n_slot].flag[1][5] = (flow[n_slot].flag[1][5]
>> 1) + ( flow[n_slot].flag[1][5] >> 2 )
    + (flow[n_slot].flag[1][5] & 1 ) ;
}
// update flag counters when ip1 is source
if( flags & 0xffffffc0 ) {
    flow[n_slot].flag[1][0] ++ ; // flags >> 0x3f//
}
SYN-FIN et al
    flow[n_slot].flag[1][1] += (flags >> 2) & 0x01 ; // RESET
    flow[n_slot].flag[1][2] += (flags >> 5) & 0x01 ; // URGENT
    flow[n_slot].flag[1][3] += ((~flags >> 4) & (flags >> 1) &
0x01) ; // not-ACK & SYN
    flow[n_slot].flag[1][4] += (( flags >> 4) & (flags >> 1) &
0x01) ; // ACK & SYN
    flow[n_slot].flag[1][5] += (( flags >> 4) & flags &
0x01) ; // ACK & FIN
    flow[n_slot].flag[1][6] |= (tcp_buf[18] | tcp_buf[19]) ; //
URG pointe
}
// ===== APPLICATION LAYER CHECK =====
app_0 = 4 * (tcp_buf[12] >> 4) ; // TCP options between 20 and
data_0
app_len = rec_len - ip_options_1 - both_hdr - app_0 ; // index in
tcp_buf, rec_len - all hdrs
if( app_len >= 5 ) {
    if( ! memcmp( &tcp_buf[ app_0 ], "ISON ", 5 )) log_pkt = 1 ;
    if( ! memcmp( &tcp_buf[ app_0 ], ":irc.", 5 )) log_pkt = 1 ;
}
// host[hs].server |= IRC ;
// host[hd].client |= IRC ;
} // end - app_len > 4

break ; // end TCP

case 17 : // *** UDP ***
{
    int j, k, d ;
    data_0 = 8 ; // 1st byte of data in tcp_buf
    data_1 = rec_len - ip_options_1 - both_hdr ; // last byte of data
in tcp_buf
    d = rec_len - ip_options_1 - both_hdr - 8 ;
    n_udp++ ;
    if( ip0 == src_addr) j = 0 ; // index 'j' is source
    else j = 1 ;

```

LANcope Code

```

k = 1 - j ;

flow[n_slot].pkts[j]++ ;
flow[n_slot].bytes[j] += bytes ; //does not include TCP/IP hdr
if( d <= SHORT_UDP_MAX ) {
    flow[n_slot].flag[j][BAD] ++ ;
    log_pkt = 1 ;
}
if((flow[n_slot].pt[k] == 7) || (flow[n_slot].pt[k] == 19)) { //
echo and chargen
    flow[n_slot].flag[j][BAD] ++ ;
    log_pkt = 1 ;
}

}
break ; // end of UDP

case 1 : // *** ICMP *** - no flows for ICMP
    n_icmp++ ;
    //char icmp_type[18][20] = {"Echo_Reply", "Type_1", "Type_2", "Des_Unreach",
    "Quench", "Redirect", \
    //"Type_6", "Type_7", "Echo_Req", "Rtr_Advert", "Rtr_Solic", "Time_Out",
    "Param_Prob", \
    //"Timestamp", "Time_Reply", "Info_Request", "Info_Reply", "Type_>16"} ;

    if( hs > 0 ) {
        host[hs].pkts_ot++ ;
        host[hs].bytes_ot += bytes ; // does not include IP
hdr
        host[hs].bytes_ot_pp += bytes_hdr ; // includes IP hdr
        host[hs].pkts_ot ++ ;
        if( tcp_buf[0] == 8 ) { // Echo_Req
            record_probe( hs, des_addr, des_port ) ; // hs is
source of probe, des_addr is destination
            host[hs].pings ++ ;
            if( host[hs].pings > 200 ) {
                host[hs].alerts |= PING_ALERT ;
            }
        }
        pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
//xx
        ; // ping probe
        scan_pair( src_addr, des_addr, PING_SCAN, 0)
        pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
    }

    if( hd > 0 ) {
        host[hd].pkts_in++ ;
        host[hd].bytes_in += bytes ; // does not include IP
hdr
        host[hd].bytes_in_pp += bytes_hdr ; // includes IP hdr
        host[hd].pkts_in ++ ;

        if( tcp_buf[0] == 0 ) { // Echo_Reply
            host[hd].pings ++ ;
            record_probe( hd, src_addr, des_port ) ; // hd is
source of probe, src_addr is destination
            if( host[hd].pings > 100 ) {
                host[hd].alerts |= PING_ALERT ;
            }
        }
        //xx pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
//xx
        scan_pair( des_addr, src_addr, PING_SCAN, 0)
        ;
        //xx pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
    }
    if( tcp_buf[0] == 3 ) {

```

```

                                LANcope Code
                                host[ hd ].rejects ++ ; // Des_Unreach
                                log_pkt = 1 ;
                                record_probe( hd, src_addr, des_port ) ; // hd is
source of probe, src_addr is destination
                                } // end - des unreachable

                                if( tcp_buf[0] == 11 ) {                                // Time-Out
Notice
                                register unsigned int d_ip, i_pt ;
                                register unsigned short d_pt ;
                                host[hd].traces ++ ;
                                d_ip = s2i( &tcp_buf[ 24 ] ) ; // original
destination in ICMP 8 + ip2[16]
                                i_pt = 10 + 4*(tcp_buf[8] & 0x0f) ; // index in
tcp_buf to original src port number
                                d_pt = 256 * tcp_buf[ i_pt ] + tcp_buf[ i_pt + 1] ;
                                record_probe( hd, d_ip, d_pt ) ;
                                if( host[hd].traces > 100 ) {
pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
                                scan_pair( des_addr, d_ip, ICMP_TO, 0) ; //
20 + length of IP header
pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
                                } // end hd > 0

//                                data_0 = 8 ;
//                                data_1 = rec_len - ip_options_1 - both_hdr ; // last byte of data in
tcp_buf
                                break ; // end of ICMP

                                default:                                not_tui++ ; // count packets not TCP, UDP, or ICMP
(discarded)
                                } // end of switch on ip_buf[9] - layer 4 protocol

// ===== READ NEXT PACKET RECORD
=====
read_next:
                                ; // log all flows and pkts

                                if(f_demo || log_pkt || flow[n_slot].state & WATCH_FLOW ) {
write tcpdump packet header                                fwrite( snp_buf, sizeof(char), 24 , log_pkt_file) ; //
write tcpdump LAN header                                fwrite( lan_buf, sizeof(char), lan_hdr , log_pkt_file) ; //
write tcpdump IP & TCP header                                fwrite( ip_buf , sizeof(char), tcp_all , log_pkt_file) ; //
                                }
if( f_verbose == 3 ) { printf(" Pkt %u done at %u\n", np, t_run ) ; fflush(stdout)
; }
pthread_mutex_unlock( &mp_hosts) ; // ### unlock hosts[]
pthread_mutex_unlock( &mp_flows) ; // ### unlock flows[]

                                if(f_file) { // -----timing control for FILE
INPUT
                                if( t_run > t_pause ) {
                                if( f_verbose == 2) printf(".") ; // should be 30
.'s then \n
                                t_pause += 3 ;
                                Page 25

```

```

                                LANcope Code
                                }
                                if((t_run + t_zero) > t_next_cf) {
                                    t_next_cf += CLASS_FLOW_INT ;
                                    if( f_verbose == 2) printf("\n") ;
                                    fflush( stdout ) ;
                                    pthread_mutex_unlock( &mp_class_flow ) ; // clear
and continue
                                if( f_verbose == 2) printf( "  ## process_pkts -
blocking for other threads. ##\n" ) ; fflush( stdout ) ;
                                sleep(2) ; // give class_flows() a chance to run
                                pthread_mutex_lock( &mp_class_flow ) ; // block
until class_flow() is done
                                }
                                } // end f_file true
                                n = fread( (void *) snp_buf, 4, 6, infile) ; // read
snoop record header into snp_buf[ ]
                                if( n<6) { printf("\nEOF at Packet %u\n", np) ; break ; }
read_ip_buf:
                                if( snoop ) { // snoop
                                    rec_len = ((unsigned long) snp_buf[8] << 24) | ((unsigned long)
snp_buf[9] << 16) | \
                                                ((unsigned long) snp_buf[10] << 8) |
((unsigned long) snp_buf[11] ;
                                    t_read = ((unsigned long) snp_buf[16]<<24) | ((unsigned long)
snp_buf[17] << 16) | \
                                                ((unsigned long) snp_buf[18]<<8) | (unsigned long)
snp_buf[19] ;
                                } else { // tcpdump
                                    rec_len = ((unsigned long) snp_buf[11] << 24) | ((unsigned long)
snp_buf[10] << 16) | \
                                                ((unsigned long) snp_buf[9] << 8) |
((unsigned long) snp_buf[8] + 24 ;
                                                                // tcpdump does not
include it's 24
                                    t_read = ((unsigned long) snp_buf[3] << 24) | ((unsigned long)
snp_buf[2] << 16) | \
                                                ((unsigned long) snp_buf[1] << 8) |
((unsigned long) snp_buf[0] ;
                                }
                                if( rec_len > snp_rec_max ) {
                                    printf("\n*** FILE OUT OF SYNC *** after %u, rec_len %u, not
%u\n\n", np, rec_len, snp_rec_max);
                                    break ;
                                }
                                n = fread( (void *) lan_buf, 1, lan_hdr , infile); // read IP+TCP or
UDP header into lan_buf[ ]
                                if ( n < lan_hdr ) {
                                    printf("EOF after Packet %u", np) ;
                                    break ;
                                }
                                tcp_all = rec_len - both_hdr ;
                                n = fread( (void *) ip_buf, 1, tcp_all , infile) ; // read IP+TCP
header into ip_buf[ ]
                                if ( n < tcp_all ) {
                                    printf("EOF after Packet %u\n", np) ;
                                    break ;
                                }
                                np++ ;

```

```

LANcope Code
//if( (np % 100000) == 0 ) { printf(".\008") ; fflush(stdout) ; } // progress dots
// t_check = time(NULL) ;
// printf("np: %u, n_flow: %u, active: %u, max: %u, t_run: %u, Real t: %u\n",
// np, n_flow, n_active, n_active_max, t_run, (t_check -
t_now)) ; ///DEBUG
// fflush(stdout) ;

} // ##### break -> END OF LOOP TO READ PACKETS
#####

if( (f_file == 0) && (running == 1) ) { // == TRY TO RESTART TCPDUMP
printf( "\n ### TCPDUMP STOPPED SENDING DATA, will try to restart. np: %u, t_run: %u\n", np, t_run);
fclose( infile ) ;
for( i = 0 ; i < 3600 ; i++ ) {
if( running != 1 ) break ;
if( start_tcpdump( ) == 0 ) { // returns '0' if tcpdump
restarted successfully
n = fread( (void *) snp_hdr, 4, 6, infile) ; //
read new file header
goto restart_here ;
}
else sleep( 24 ) ;
fclose( infile ) ;
} // end if f_file == 0 -> realtime
}
running = 2 ; // RESTART NOT SUCESSFUL, or f_file, => close all threads

// if( f_file) pthread_mutex_unlock( &mp_class_flow ) ; // clear and let
process_pkts continue
printf("Thread process_pkts ending at t: %u, np: %u\n", t_run, np) ;
return ;
} // ### end process_pkts ###

int start_tcpdump( void ) // ===== START (and RESTART) TCPDUMP
=====
{
FILE * tmpfile ;
register int i, j ;
char c, command[200], select[120] ;
if( setuid(0) != 0 ) {
printf( " ### CAN NOT SETUID(0) and START tcpdump -
TERMINATING ###\n") ;
return( 1 ) ;
}
sprintf(command,"date\n");
printf(" system commands: %s", command) ; // this will
print date and time
system(command);

kill_tcpdump() ; // kill any present instance of tcpdump
sleep(1) ;
sprintf(command, "/usr/bin/mkfifo myfifo");
printf(" : %s\n", command); // this will create a new
"myfifo"
if( system(command) ) printf( "#### FAILED ####"); // reset
interface eth1

sprintf(command, "/sbin/ifconfig eth1 down promisc up");
printf(" : %s\n", command) ; // reset eth1 to promiscuous
and start it up
if( system(command) ) printf( "#### FAILED ####"); // reset

```


LANcope Code

```
interface eth1
```

```
sprintf(command, "/bin/nice -20 /usr/sbin/tcpdump -lni eth1 -s 120 -w myfifo 'ip'
1>log_tcpdump 2>>log_tcpdump &");
printf(" : %s\n", command) ; // kill( (pid_t) k, SIGQUIT ) ;
sleep(1) ;
if( 0 == system(command)) { // start 'tcpdump' on interface eth1
    if((infile = fopen ("myfifo","rb"))!=NULL) { // OPEN
INPUT FILE // File opening for input from TCPDUMP
        printf(" tcpdump STARTED SUCESSFULLY.\n") ;
        return( 0 ) ;
    }
}
printf(" tcpdump START or 'myfifo' OPEN - FAILED.\n") ;
return( 1 ) ;
} // end start_tcpdump
```

```
void kill_tcpdump( void ) {
```

```
    int i, j, k ;
    char command[100], select[100], c ;
    FILE *tmpfile ;
```

```
        system("/bin/ps -e | /bin/grep 'tcpdump' > tempfkiebtj" ) ; //
see if TCPDUMP running
```

```
    if( (tmpfile = fopen("tempfkiebtj","r")) != NULL) {
```

```
        for( i = 0 ; i < 99 ; i++ ) {
            if( ( c = getc(tmpfile)) != EOF) && ( c >= 32) ) {
                select[i] = c ;
            }
        }
    }
    else {
        select[i] = 0 ;
        break ;
    }
}
fclose(tmpfile) ;
system("/bin/rm -f tempfkiebtj") ;
```

```
end, if any
```

```
while( (select[i] <= ' ') && ( i > 0) ) { // remove spaces at
    select[i] = 0 ; i-- ;
}
```

```
select[i-7] == ' ') ) {
    if( (i>7) && ( 0 == strcmp("tcpdump", &select[i-6])) && (
```

```
        j = -1 ;
        for( i = 0 ; i < 99 ; i++ ) {
            if((select[i] == ' ') && ( j >=0)) {
                select[i] = 0 ;
                break ;
            }
            if((select[i] != ' ') && ( j < 0)) j = i ;
        }
    }
    k = atoi(&select[j]) ;
    if( (k > 0) && ( k <= 99999) ) {
        sprintf(command, "/bin/kill %d", k);
        printf(" system command sent to kill
tcpdump: %s ", command) ; // kill( (pid_t) k, SIGQUIT ) ;
        if( system(command) ) printf(" #### FAILED
####\n"); // kill tcpdump, if necessary
        else printf(" --- SUCCESS ---\n");
```

```

                                LANcope Code
                                sleep(1) ;
                                }
                                } // if file tempfkiebtj opened - tcpdump now "killed" if it was
still running

                                sprintf(command, "/bin/rm -f myfifo");
                                printf(" : %s ", command) ; // this will remove "myfifo"
(and junk still in it)
                                if( system(command) ) printf(" #### FAILED ####\n"); // reset
interface eth1
                                else printf(" --- SUCCESS ---\n");
} // end - kill_tcpdump()

void usage( void ) {
    printf("\nUsage: lancope in-file out-file flags\n");
    printf(" Output file extension should be .csv for StarOffice, .txt for
Excel\n");
    printf(" Output file = '-' means date-derived file, yymmddhh.txt , e.g.
'00081515.txt\n" );
    printf(" Flags: d = dotted decimal, e = encrypt local IPs, a = write all
flows\n");
    printf(" f = input from file, s = split_path, o = demo, all on
alert & traffic\n");
    printf(" n = no-read old profiles\n");
    printf(" A file, 'lancope_config.txt' must be in the default directory
with config info\n");
    exit(-1) ;
}

unsigned long s2i(unsigned char bb[4]) //msB first string to uns long int
{
    unsigned long j ;
    j = ((unsigned long) bb[0]) << 24 | ((unsigned long) bb[1]) << 16 | \
        ((unsigned long) bb[2]) << 8 | ((unsigned long) bb[3]) ;
    return(j);
} //end s2i()

unsigned long b2i(unsigned char bb[4]) //lsB first string to uns long int
{
    unsigned long j ;
    j = ((unsigned long) bb[3]) << 24 | ((unsigned long) bb[2]) << 16 | \
        ((unsigned long) bb[1]) << 8 | ((unsigned long) bb[0]) ;
    return(j);
} //end b2i()

long find_slot( unsigned long ip0, unsigned long ip1, long port0, long port1)
// returns 0 if no slot available, i if entry exists // mp_flows LOCKED
{
    unsigned long x, i, i_mark, n, index, h, flows_max = SLOTS, unlock = 0 ;
    int hihi = 0 , ftp_server = 0 ;
    if( ! pthread_mutex_trylock( &mp_flows ) ) {
        printf(" ### find_slot() without mutex m_flow being set. t:
%u, Running: %u\n", t_run, running);
        unlock = 1 ;
    }
}

```

```

LANcope Code
***/
x = ip0 ^ (ip1<<11)^(ip1>>21) ; /*** make index from DA, SA, check Port
index = x ;
for (i = SHIFT ; i < 32 ; i += SHIFT ) {
    x = x >> SHIFT ;
    index ^= x ;          // XOR bytes together
}
index = index & MASK ; // limit to right SHIFT bits
index++ ;              // index can be 1 to 2^n +1

// --- look for matching connection or first empty slot
scan_max = 0 ; // count max ports connected
if(( port0 > 1023) && (port1 > 1023)) hihi = 1 ;
if(( port0 == 21) || ( port0 == 20 )) ftp_server = 1 ;
if(( port1 == 21) || ( port1 == 20 )) ftp_server = 2 ;

if( flow[index].root) { // root not empty, run through list, look for
matching flow
    i = flow[index].root ;
    do {
        register int nomatch, type ;
        nomatch = 1 ; // test match below
        if( (flow[i].ip[0] == ip0) && (flow[i].ip[1] == ip1) ) { //
nomatch if IP's different
            scan_max++ ; //max ports open
            ip0-ip1
            type = ( flow[i].state >> 1 ) & 3 ; // type = 0, 1,
            2

            if((flow[i].service & HI_HI)&&!(flow[i].service &
FTP_ANY))) {
                if( ftp_server == 1 ) flow[i].state |= FTP_SER_0 ;
                // new flow is marked for FTP_0/1
                if( ftp_server == 2 ) flow[i].state |= FTP_SER_1 ;
                // and the old one has high-high ports
            }

            if(( hihi ) && (! ftp_server)) {
                if(flow[i].state & FTP_SER_0) ftp_server = 1 ; //
old flow is marked for FTP_0/1 and
                if(flow[i].state & FTP_SER_1) ftp_server = 2 ; //
the new one has high-high ports
            } // end - if FTP check

            switch( type ) {
            case 0 :
                if( (flow[i].pt[0] == port0) &&
(flow[i].pt[1] == port1) ) { // exact port match
                    nomatch = 0 ;
                    break ;
                }
                if( flow[i].pt[1] == port1) {
                    nomatch = 0 ;
                    flow[i].state |= 0x2 ; // type => 1

                    ip1 is Server, ip0 is client
                    flow[i].pt_min = flow[i].pt_max =
                    flow[i].pt[0] ;
                    flow[i].pt_min = port0 ;
                    flow[i].pt_max = port0 ;

                    if( port0 < flow[i].pt_min )
                    if( port0 > flow[i].pt_max )
                    break ;
                }
            }
        }
    } while (i != 0)
}

```

```

LANcope Code
    }
    if( flow[i].pt[0] == port0) {
        nomatch = 0 ;
        flow[i].state |= 0x4 ; // type => 2

        flow[i].pt_min = flow[i].pt_max =
        if( port1 < flow[i].pt_min )
        if( port1 > flow[i].pt_max )
        break ;
    }
    break ;
case 1 : // ip0 is client
    if( flow[i].pt[1] == port1) {
        nomatch = 0 ;
        if( port0 < flow[i].pt_min )
        if( port0 > flow[i].pt_max )
        break ;
    }
    break ;
case 2 : // ip1 is client
    if( flow[i].pt[0] == port0) {
        nomatch = 0 ;
        if( port1 < flow[i].pt_min )
        if( port1 > flow[i].pt_max )
        break ;
    }
    break ;
} // end switch( type )
}

if( nomatch ) {
    if( (flow[i].up)) {
        i = flow[i].up;
    } else {
        break ; // break out of while(1) - end of
list, no match
    }

} else { // there was a match
    goto update_flow ; // slot for flow already exists
}
} while( 1) ; // break out (goto) when end of list or match found

i_mark = i ; // index of last entry in list - NEW HOST ENTRY
for( n = 0 ; n < RANGE ; n++) {
    i += 5 + n ;
    if( i >= SLOTS ) i = i - SLOTS + 1; // can not use i = 0
    if( flow[i].down == 0 ) { // empty, use for new entry
        flow[i_mark].up = i ;
        flow[i].down = i_mark ;
        goto new_flow ;
    }
}

```

LANcope Code

```

    }
    n_full++;
    if( unlock ) pthread_mutex_unlock( &mp_flows) ; // ### unlock
flows[]
    return( 0 ) ; // flow data sub-structure full
}

else { // flow[index].root == 0, search for any empty slot for NEW
ENTRY, 1st for this ip0-ip1
    i = index ;
    for( n = 0 ; n < RANGE ; n++) {
        i += 5 + n ;
        if( i >= SLOTS ) i = i - SLOTS + 1; // can not use i = 0
        if( flow[i].down == 0 ) {
            flow[index].root = i ;
            flow[i].down = index ;
            goto new_flow; // new leaf
        }
    }
    n_full++;
    if( unlock ) pthread_mutex_unlock( &mp_flows) ; // ### unlock
flows[]
    return( 0 ) ; // flow data sub-structure full
}

new_flow:
    n_flow++;
    n_active++;
    if( n > n_max) n_max = n ; // check hash efficiency
    flow[i].up = 0 ;
    flow[i].ip[0] = ip0 ;
    flow[i].ip[1] = ip1 ;
    flow[i].pt[0] = port0 ;
    flow[i].pt[1] = port1 ;
    flow[i].start = t_run ;
    flow[i].state = transport & 0x1 ; // 0 -> TCP, 1 -> UDP, Type = 0
    if( f_loose) flow[i].state |= LOOSE ;

    if( ftp_server ) {
        flow[i].service = 21 ;
        if( ftp_server == 1) flow[i].state |= FTP_SER_0 ; // set bit
        if( ftp_server == 2) flow[i].state |= FTP_SER_1 ; // set bit
    }
    if( hihi) flow[i].state |= HI_HI ; //
update_flow:
    flow[i].last = t_run ;
    if( unlock ) pthread_mutex_unlock( &mp_flows) ; // ### unlock flows[]
    return( i ) ;
} // end find_slot()

void class_flow( void ) { // ##### CLASSIFY FLOW ###locks flows, then hosts
#####
// =====
    unsigned int i, j, k, n, s1 = 0, udp, error_count = 0, alarms0 = 0, h0 = 0 ;
    unsigned long h ;
    unsigned int pps0, pps1, flows_ended, n_fprint, mm_bit, mcast_bit, odd_bit,
bcast_bit, wai ;
    char reason[20] ;
    time_t t_here, t_next_prof ;
    int this_hour, last_hour, clear ;

t_wa_last = t_zero ;

```

```

                                LANcope Code
mm_bit = port_mask[ 2 * UDP_PORT_OFFSET +1 ] ; // bit for multimedia ,
psedo-port = 2049
mcast_bit = port_mask[ 2 * UDP_PORT_OFFSET +2 ] ; // bit for multicast service,
psedo-port = 2050
bcast_bit = port_mask[ 2 * UDP_PORT_OFFSET +3 ] ; // bit for broadcast service,
psedo-port = 2051
odd_bit = port_mask[ 2 * UDP_PORT_OFFSET +4 ] ; // bit for odd service,
psedo-port = 2052
printf("Thread class_flow start at t: %u, np: %u, flows: %u\n",
      (unsigned int) *(&t_run), (unsigned int) *(&np) , (unsigned
int) *(&n_flow) ) ;
if( *(&running) == 1 ) {
    {
        unsigned int cfi = CLASS_FLOW_INT ; // cfi = 30 s
        unsigned int wai = WEB_ALERT_INT ; // wfi = 900
        t_next_cf = *(&t_zero) + 0.5 * cfi ;
        t_next_cf = t_next_cf + cfi - (t_next_cf % cfi) ; // moves to
nearest even value
        t_next_web = t_zero + 1.5 * wai ;
        t_next_web -= ((t_next_web % wai) + 2) ; // moves to nearest even
value * wfi
        t_next_prof = t_next_web + 0.5 * wai - 2 ; // save profiles between
web_alert calls
        t_bs_last = t_zero ; // moves to nearest even value *
    }
}
// printf(" class_flow() - t_run: %u, t_here: %u, t_next_cf: %u, t_next_web:
%u\n",
//      *(&t_run), *(&t_run) + t_zero , t_next_cf, t_next_web);
// fflush( stdout ) ;

last_hour = 100 ; // will be initial set later - hour of the day, 1 - 23

while( running) { // 'running' == 1: loop, 'running' == 2: execute once and return
    register unsigned int host0 , alarm0, age ;

    if( f_file) {
        sleep(2) ;
        if( f_verbose == 2) printf("Class_Flow approaching mutex lock.
t_run: %u\n", *(&t_run) ) ;
        fflush( stdout ) ;
        pthread_mutex_lock( &mp_class_flow) ; // ### block process_pkts()

        if( f_verbose == 2) printf("Class_Flow passed mutex lock.
t_run: %u\n", *(&t_run) ) ;
        fflush( stdout ) ;
    }

    if( f_file) t_here = *(&t_run) + t_zero ; // t_run always starts at 1
    else t_here = time( NULL ) ; // if realtime, use real time

    while((t_here < t_next_cf) && (running == 1) && (! f_file) ) {
        sleep(1) ; // stall if running == 1, then check 'running' and
(t_here < t_next_cf)
        if( f_file) t_here = *(&t_run) + t_zero ;
        else t_here = time( NULL ) ;
        if( t_here >= t_next_cf) break ;
    }
    if( f_file == 0) t_run = t_here - t_zero ;

    if( running == 0 ) break ;

```

```

                                LANcope Code
    t_next_cf += CLASS_FLOW_INT ;
    if(f_verbose) {
        printf("* Thread class_flow operating at t: %u, next: %u, np: %u,
flows: %u\n",
        t_here - t_zero, t_next_cf - t_zero, (unsigned int) *(&np), (unsigned
int) *(&n_flow));
        if(f_verbose > 1 )      fflush( stdout ) ;
    }
    n_fprint = flows_ended = 0 ;

    for( i = 1 ; i < SLOTS ; i++ ) {
        unsigned long quiet, p, h[2] ;
        int s[2], c[2], list ;

// S/C determined by SYN's and SYN-ACK's

        if(flow[i].down) { // flows that exist
pthread_mutex_lock( &mp_flows) ; // ### lock flows[]

            if(flow[i].down) { // confirm after locking

                reason[0] = 0 ;
                clear = 0 ;
                quiet = 70 ; // udp and tcp single die if quiet > 20 sec
                age = 30 ;
                list = 0 ;
                if( flow[i].state & UDP_FLOW) udp = UDP_PORT_OFFSET ; // index offset for
port_name
                else udp = 0 ;

                if( (!(flow[i].state & UDP_FLOW)) && (flow[i].pkts[0] >
flow[i].flag[1][RST]) &&
                    (flow[i].pkts[1] > flow[i].flag[0][RST]) ) quiet = FLOW_DEAD ;
                // if TCP and packets in + packets out > resets returned wait FLOW_DEAD
(300 s)

                if( ( t_run > ( flow[i].last + quiet ) ) || (running==2) ) { // if flow has
been silent for 'quiet' seconds
                    flows_ended++ ;
                    clear = 1 ;
                }
                // end - check to 'clear'

// ===== CHECK FOR PROBES AFTER 'AGE' =====//
if(( ! (flow[i].state & ATTACK_CHK ) ) && (t_run > (flow[i].start + age)) ){
    register long int sa = 0, da = 0 ; // If flow NOT classified, and
'old', check for probes
    unsigned char probe_type = 0 ;
    unsigned short probe_port = 0 ;
pthread_mutex_lock( &mp_hosts) ;

    flow[i].state |= ATTACK_CHK ; // set so we check once only

    for( j = 0 ; j <= 1 ; j++ ) {
        k = 1 - j ;
        probe_type = 0 ;
        h[j] = find_host( flow[i].ip[j], flow[i].bytes[j] ) ; // h[j] ->
ip[j], may be '0' if slot does not exist

```

```

                                LANcope Code
    if(!(flow[i].state & UDP_FLOW)){ // TCP - check for probes
        if( flow[i].pkts[j] && ( (flow[i].pkts[k] ==
flow[i].flag[k][RST] ) ||
                                (flow[i].pkts[j] == flow[i].flag[j][BAD]) ||
(flow[i].pkts[k] == 0 ) ) ) {
            probe_type = TCP_PROBE ;
        } // end - TCP probe check

        else if( flow[i].flag[j][BAD] + flow[i].flag[k][RST] ) { // UDP
Check RST means ICMP port unavailable
            probe_type = UDP_PROBE ;
        } // end - UDP probe check

        if( probe_type && h[j]) {
            list = 1 ; strcat( reason, "Probe " ) ;
            record_probe( h[j], flow[i].ip[k], flow[i].pt[k]); // h[j]
is source index of probe, 'k' is destination ip
pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
            scan_pair( flow[i].ip[j], flow[i].ip[k], probe_type,
flow[i].pt[k] ) ; // ip[j] hit ip[k]:pt[k]
pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
            flow[i].state |= ( PROBE | CLASSIFIED ) ; // flow has been
classified as "probe"
        } // end - probe_type > 0
    } // end - j = 0,1
    // ===== CHECK FOR ATTACKS after 'of age'

    if((!udp) && (!(flow[i].state & ATK_PROBE))){ // if TCP - check for
half-open attack
        for( j = 0 ; j <= 1 ; j++ ) {
            k = 1 - j ;

            if(( flow[i].pkts[j] > 16 ) && ( flow[i].flag[j][SYN] >
(0.75 * flow[i].pkts[j] ) ) &&
                                (flow[i].flag[k][S_A] > 4) ) { // if half-open
attack, 'j' attacking 'k'
                list = 1 ; strcat( reason, "HO_Attack " ) ; // will
list only if clear is set for this cycle
                if( h[j] ) {
                    record_probe( h[j], flow[i].ip[k],
flow[i].pt[k]); // h[j] is source of probe, des_addr is destination ip
                    host[ h[j] ].alerts |= HO_ATTACK ;
                    host[ h[j] ].concern += HO_ATTACK_INIT_CI ;
                } // end - find_host() ok
pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
                scan_pair( flow[i].ip[j], flow[i].ip[k], HALF_OPEN,
flow[i].pt[k] ) ; // type 8 -> circle packet
pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
                flow[i].state |= ( CLASSIFIED | ATTACK ) ; // flow
has been classified as "attack"
            } // end - Half-Open Attack found
        } // end - for j = 0,1 and k = 1,0
    } // end - check for half-open (lots of SYN's evoking SYN-ACK's)
pthread_mutex_unlock( &mp_hosts) ;
} // end - #### check for probes & attacks after 'age' ####

                                // ===== END-OF-LIFE FLOW
CLASSIFICATION ===== //

if( (!(flow[i].state & CLASSIFIED)) && clear ) { // ### CLASSIFY FLOW, - DETERMINE
SERVER/CLIENT ###
    c[0] = c[1] = s[0] = s[1] = 0 ;

```


LANcope Code

```

pthread_mutex_lock( &mp_hosts) ;
    h[0] = find_host( flow[i].ip[0], flow[i].bytes[0] ) ; // h[j] -> ip[j], may
be '0' if slot does not exist
    h[1] = find_host( flow[i].ip[1], flow[i].bytes[1] ) ;

if(f_verbose==4)
{
    printf(" -- Flow Ended. t_run: %u, Flow[%u].last: %u, quiet: %u,
t[NOW]-t_zero: %u\n",
        t_run, i, flow[i].last, quiet, t_here - t_zero ) ;
    printf(" -- Type:%u, FTP: %x, Port0: %u, Port1: %u, Serv: %u, Pmin: %u, Pmax: %u,
syn0: %u, sa0: %u, syn1: %u, sa1: %u\n",
        (flow[i].state & 6) >> 1, (flow[i].state & FTP_ANY) >> 12,
flow[i].pt[0],flow[i].pt[1],flow[i].service,flow[i].pt_min,
flow[i].pt_max,flow[i].flag[0][SYN],flow[i].flag[0][S_A],flow[i].flag[1][SYN],flow[i]
].flag[1][S_A] ) ;
}

for( j = 0 ; j <= 1 ; j++ ) { // ##### TCP - Check ip[j] for Port Probing based
on flow data for LOOSE flow #####
    k = 1 - j ;
    if( h[j] ) {
        if(flow[i].state & LOOSE) { // LOOSE == Handle case where not
all packets have been seen
            if(flow[i].scans >= SCAN_MAX) {
                if(flow[i].flag[k][RST] >= (flow[i].pkts[k] /2 + 2))
                { // if the other guy sent many resets
                    host[h[j]].pt_scans++ ;
                    list = 1 ; strcat( reason, "Pt_Scan2") ;
                    flow[i].state |= PROBE ;
                    record_probe( h[j],
flow[i].ip[k],flow[i].pt[k] ) ; // h[j] is source index of probe, des_addr is
destination ip
                    pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
scan_pair( flow[i].ip[j], flow[i].ip[k],
TCP_PORT_SCAN, 0 ) ; // ip[j] hit multi-ports
                    pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
                } }
                else { // not LOOSE
                    if((flow[i].scans >= SCAN_MAX) || (flow[i].flag[k][RST] ==
flow[i].pkts[k])){ // >SCANMAX or all RSTs
                        if(flow[i].flag[k][RST] >= (flow[i].pkts[k] /2 + 1))
                        { // if the other guy sent more resets
                            host[h[j]].pt_scans++ ;
                            list = 1 ; strcat( reason, "Pt_Scan2 ") ;
                            flow[i].state |= PROBE ;
                            record_probe( h[j], flow[i].ip[k],
flow[i].pt[k]); // h[j] is source index of probe, 'k' is destination ip
                            pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
scan_pair( flow[i].ip[j], flow[i].ip[k],
TCP_PORT_SCAN, 0 ) ; // ip[j] hit ip[k]:pt[k]
                            pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
                        } }
                    } // end - not LOOSE
                } // end - h[j]
            } // end - j = 0,1 k= 1,0 ---- TCP check for Port Probes, not ATK_PROBE

if( flow[i].state & FTP_ANY ) { // ===== FTP ===== //
    if( flow[i].state & FTP_SER_0) s[0] = c[1] = 1 ;
    else if( flow[i].state & FTP_SER_1) s[1] = c[0] = 1 ;
} // end FTP

```

LANcope Code

```

else { // not FTP
    for( j = 0 ; j <= 1 ; j++ ) {
        k = 1 - j ;
        if( (!flow[i].flag[j][SYN]) && (!flow[i].flag[k][S_A])
            && (flow[i].flag[j][S_A] || flow[i].flag[k][SYN])) {
            s[j] = 1 ; c[k] = 1 ; // ip[j]
        }
        is Server, ip[k] is Client based on flags
        //flag-3 is SYN, flag-4 is SYN-ACK (S_A)
        if( ! (flow[i].state & 0x6)) { // type 0 - both ports constant
            if( c[j] == 1 ) flow[i].pt_min = flow[i].pt_max =
            flow[i].pt[j] ; // ip0 is client
        }
        } // end - j = 0,1 k=1,0

        // S/C determined by flow Type for UDP and TCP (if not FTP)
        if( flow[i].state & 0x2 ) c[0] = s[1] = 1 ; // type 1, ip0 is client.
        Disagree with flags -> port scan
        if( flow[i].state & 0x4 ) c[1] = s[0] = 1 ; // type 2, ip1 is client

        if( (! udp) && (flow[i].state & LOOSE) && (! c[0]) && (! s[0]) ) { // loose
        -> syn and s-a may be lost
            if( (flow[i].pt[0] < LOW_PT_MAX) && (flow[i].pt[1] >= LOW_PT_MAX) )
            { s[0] = c[1] = 1 ; }
            if( (flow[i].pt[1] < LOW_PT_MAX) && (flow[i].pt[0] >= LOW_PT_MAX) )
            { s[1] = c[0] = 1 ; }
            if((flow[i].pt[0]==22)|| (flow[i].pt[0]==37)|| (flow[i].pt[0]==53))
            s[0] = c[1] = 1 ;
            if((flow[i].pt[1]==22)|| (flow[i].pt[1]==37)|| (flow[i].pt[1]==53))
            s[1] = c[0] = 1 ; // ssh (22) - low client numbers
            if((flow[i].pt[0]==512)|| (flow[i].pt[0]==513)|| (flow[i].pt[0]==514))
            s[0] = c[1] = 1 ; // login, sh, prt also
            if((flow[i].pt[1]==512)|| (flow[i].pt[1]==513)|| (flow[i].pt[1]==514))
            s[1] = c[0] = 1 ;
        }

        if(f_verbose==4) {
            printf(" -- Before. s0: %u, c0: %u, s1: %u, c1 :%u", s[0], c[0]
            ,s[1], c[1] ) ;
        }

        // ----- Last_Resort to Determine who (0 or 1) is the Server
        if(( !c[0]) && (!s[0])) {
            for( j = 0 ; j < 2 ; j++ ){ // if one port is a common server port,
            assume it is the server port
                k = 1 - j ;
                if(( flow[i].pt[j] < UDP_PORT_OFFSET ) && ( port_mask[
                flow[i].pt[j] ] )) { // if either port is a common local server port
                    s[j] = c[k] = 1 ;
                }
            }
        }
    } // end - find c[] and s[] when not FTP

    if( c[0] && ( flow[i].pt_min < flow[i].pt[0])) flow[i].pt_min =
    flow[i].pt[0] ; // TELLS IF CLIENT IS 'LOW'
    if( c[1] && ( flow[i].pt_min < flow[i].pt[1])) flow[i].pt_min =
    flow[i].pt[1] ;
    if( s[0] && ( ! flow[i].service) ) flow[i].service = flow[i].pt[0] ; //
    TELLS IF SERVER IS 'LOW' OR 'HIGH'
    if( s[1] && ( ! flow[i].service) ) flow[i].service = flow[i].pt[1] ;

    if(f_verbose==4) printf(" After. s0=%u, c0=%u, s1=%u, c1=%u, Service: %u,
    Page 37

```

```

                                LANcope Code
Port_min: %u\n", s[0], c[0], s[1], c[1],
            flow[i].service, flow[i].pt_min) ;

// ===== END OF SECTION THAT DETERMINES WHO IS HOST, WHO IS SERVER
=====//

host0 = alarms0 = 0 ;

for( j = 0 ; j < 2 ; j++ ){
    k = 1 - j ; // j,k = 0,1 and 1,0 ===== 'j' is this host, 'k' is
other host

    if( ! (flow[i].state & ATK_PROBE )) { // if not already known to be a probe
from early check

        // ##### TCP - Check ip[j] for Port Probing based on flow data for LOOSE flow
        #####

        if(flow[i].state & LOOSE) { // LOOSE === Handle case where not
all packets have been seen
            if(flow[i].scans >= SCAN_MAX) {
                if(flow[i].flag[k][RST] >= (flow[i].pkts[k] / 2 + 2))
            { // if the other guy sent many resets
                host[h[j]].pt_scans++ ;
                list = 1 ; strcat( reason, "TCP_Pt_Scan " ) ;
                flow[i].state |= PROBE ;
                record_probe( h[j],
flow[i].ip[k], flow[i].pt[k] ) ; // h[j] is source index of probe, des_addr is
destination ip
                pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
                scan_pair( flow[i].ip[j], flow[i].ip[k],
TCP_PORT_SCAN, flow[i].pt[k] ) ; // ip[j] hit ip[k]:pt[k]
                pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
                } }
            else { // not LOOSE
                if((flow[i].scans >= SCAN_MAX) || (flow[i].flag[k][RST] ==
flow[i].pkts[k])){ // >SCANMAX or all RSTs
                    if(flow[i].flag[k][RST] >= (flow[i].pkts[k] / 2 + 1))
            { // if the other guy sent more resets
                host[h[j]].pt_scans++ ;
                list = 1 ; strcat( reason, "TCP_Pt_Scan " ) ;
                flow[i].state |= PROBE ;
                record_probe( h[j], flow[i].ip[k],
flow[i].pt[k]) ; // h[j] is source index of probe, 'k' is destination ip
                pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
                scan_pair( flow[i].ip[j], flow[i].ip[k],
TCP_PORT_SCAN, flow[i].pt[k] ) ; // ip[j] hit ip[k]:pt[k]
                pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],
                } }
            } // end - not LOOSE
        } // end - TCP check for Port Probes, not ATK_PROBE
    } // end j=0,1 k=1,0

for( j = 0 ; j < 2 ; j++ ){
    // === 'TOUCHING' === mark hosts that send
data to high CI host
    k = 1 - j ; // j,k = 0,1 and 1,0 ===== 'j' is this host, 'k' is
other host

    if( host[h[j]].alerts & ALARM_12W) { // ALARM-1 or -2 or WATCH_HOST save
flow info
        list = 1 ;

```

LANcope Code

```

        if( host[h[j]].alerts & ALARM_2) { // ALARM-2      ### HOSTS MARKED
ALARM_1 HERE ###
        if( ( j == 1) && host0 ) { // j == 1
        // IP[0] marked ALARM-0 for sending data to bad guy
IP[1]
        host[ host0 ].alerts |= ALARM_1 ;
        host[ host0 ].alarm_t = t_here ;
        }
        if( j == 0 ) { // j == 0
        alarms0 = 1 ; // set if ip[0] is bad guy
        }
    }
    if( alarms0 && (j == 1) && flow[i].bytes[j] ) { //j==1, ip[0] is bad, data
was sent
        host[h[j]].alerts |= ALARM_1 ; // IP[1] marked ALARM-0 for talking
to bad guy IP[0]
    }

    host0 = h[j] ; // only used when j = 1, then -> ip[0] // === END
'TOUCHING' ===

    // --- if ip[j] sent a packet that was not a RESET, then add to host[j]
client or server statistics
    if(host[h[j]].last < flow[i].last) host[h[j]].last = flow[i].last ; // -- update
host 'last' time

    if(( flow[i].pkts[j] > flow[i].flag[j][RST]) && !(flow[i].state & ATK_PROBE)) { //
only if 'j' sent non-RES packets

        if( !udp ) { // TCP ip[j] <-> host[h[j]]
            if(( flow[i].pkts[j] > 0 ) && ( flow[i].pkts[k] > 0 ) ) { // multiple
TCP packets
                int common = 0 ;
                if( s[j] && (!c[j])) { // "ip[j]" -> host[h[j]] is Server
                    host[h[j]].s_flows ++ ;
                    if( (flow[i].service < UDP_PORT_OFFSET) &&
(port_mask[ flow[i].service ])) common = 1 ;
                    if ((flow[i].service < LOW_PT_MAX) || common) { //
server j is LO
                        if( !
                            host[h[j]].port_smin
) host[h[j]].port_smin = flow[i].service ;
                        if( flow[i].service < host[h[j]].port_smin )
                            host[h[j]].port_smin = flow[i].service ;
                        if( flow[i].service > host[h[j]].port_smax )
                            host[h[j]].port_smax = flow[i].service ;
                        host[h[j]].server |= port_mask[
flow[i].service ] ;
                    if(f_verbose==4)
                        printf(" Server: %d, common: %d ", j, common ) ;

```

```

LANcope Code
if(( flow[i].pt_min < LOW_PT_MAX) &&
(flow[i].service != 22) && (flow[i].service != 37)) {
    if( ! ( (flow[i].pt_min ==
flow[i].service) && ((flow[i].service==53) || (flow[i].service == 109) ))) {
        host[h[j]].bad_flow++ ; //
DNS (53) and POP2 (109) talk as peer to peer on same ports.
        list = 1 ;
        strcat( reason, "LO-LO-S") ;
        host[h[j]].alerts |=
LO_LO_CS ; // do not alert on DNS or POP2 servers connecting
        host[h[j]].concern += LO_LO_CI ;
    }
} // end server port < UDP_PORT_OFFSET
else { // Server is HIGH
    host[h[j]].server |=
HIGH_PORT_SERVER ; // appears to be high-port server
    host[h[j]].bad_flow++ ;

    if( flow[i].pt_min > LOW_PT_MAX ) {
        host[h[j]].alerts |= HI_HI_CS ; //
client k HI , port > 1023
        host[h[j]].concern += HI_HI_CI ;
        list = 1 ; strcat( reason, "HI-HI-S")
;
    }
    else {
        host[h[j]].alerts |= LO_HI_CS ;
        host[h[j]].concern += LO_HI_CI ;
        list = 1 ; strcat( reason,
"LO-HI-S") ;
    }
}

if( ! common) {
    host[h[j]].server |= odd_bit ;// bit for
odd service
    for( p =0 ; p < 10 ; p++ ) {
        if( host[h[j]].s_list[p] ==
flow[i].service ) break ;
        if( ! host[h[j]].s_list[p] ) {
            host[h[j]].s_list[p] =
flow[i].service ; // if uncommon port, add to list
            break ;
        }
    }
} // end ! common
} // end ip[j] is server

if ( c[j] && (!s[j])) { // ip[j] -> host[h[j]] is client
    int common = 0 ;
    host[h[j]].c_flows ++ ;
    if((flow[i].scans > SCAN_MAX) && (flow[i].pkts[j] >=
flow[i].pkts[k])) host[h[j]].pt_scans++ ;
    if( !
        host[h[j]].port_cmin )
        host[h[j]].port_cmin = flow[i].pt_min ;
    if( flow[i].pt_min < host[h[j]].port_cmin )
        host[h[j]].port_cmin = flow[i].pt_min ;
    if( flow[i].pt_max > host[h[j]].port_cmax )
        host[h[j]].port_cmax = flow[i].pt_max ;

    if((flow[i].service < UDP_PORT_OFFSET) &&

```

```

LANcope Code
(port_mask[ flow[i].service ])){
    common = 1 ;// if server is 'common' (in the
    .server bit map) treat as 'LO' server
}
common: %d ", j, common ) ;
    if(f_verbose==4)        printf(" client: %d,

server k is LO
    if ((flow[i].service < LOW_PT_MAX) || common) { //
        host[h[j]].client |= port_mask[
        flow[i].service ] ; // assumes port -> service
        if( flow[i].pt_min >= LOW_PT_MAX ) list = 0
    ; // NORMAL = DO NOT LIST IN FILE
        else { // client j is low
            host[h[j]].alerts |= LO_LO_CS ; //
            host[h[j]].concern += LO_LO_CI ;
            host[h[j]].bad_flow++ ;
            list = 1 ;
            strcat( reason, " LO_LO-C " ) ;
        }
    } else { // server k is HI
        host[h[j]].client |=
        HIGH_PORT_CLIENT ; // appears to be high-port server's client
        host[h[j]].bad_flow++ ;
        if( flow[i].pt_min >= LOW_PT_MAX ) {
            host[h[j]].alerts |= HI_HI_CS ; //
            host[h[j]].concern += HI_HI_CI ;
            list = 1 ;strcat( reason, " HI-HI-C
        " ) ;
        }
        else {
            host[h[j]].alerts |= LO_HI_CS ;
            host[h[j]].concern += LO_HI_CI ;
            list = 1 ;
            strcat( reason, " LO-HI-C " ) ;
        }
    }
}
    if( ! common ) {
        host[h[j]].client |= odd_bit ;// bit for
        odd service
        for( p =0 ; p < 10 ; p++ ) {
            if( host[h[j]].c_list[p] ==
            flow[i].service ) break ;
            if( ! host[h[j]].c_list[p] ) { // if
            list[p] is empty, add pt[k] to it
            host[h[j]].c_list[p] =
            flow[i].service ; // if uncommon port, add to list
            break ;
            }
        }
    } // end ! common
} // ip[j], and host[h[j]], is client
if( c[j] && s[j] ) {
    if( ! (flow[i].state & LOOSE) ) {
        host[h[j]].alerts |= PORT_SCAN2 ;
        host[h[j]].pt_scans++ ;
        host[h[j]].concern += PORT_SCAN2_CI ;
        flow[i].state |= PROBE ;
    }
}

```



```

LANcope Code
} // end stats for host ip[j], j = 0, 1 & 'Touching'
flow[i].state |= CLASSIFIED ; // flow has been classified
pthread_mutex_unlock( &mp_hosts) ; // ### unlock hosts[]
} // end - not-classified and clearing flow

if(f_verbose==4)      printf("  Clear: %u, Reason: %s\n", clear, reason ) ;

if(clear) {           // ===== END-OF-FLOW ANALYSIS (beyond
client-server) ===== //
    if( f_verbose == 3) {printf(" End-of-Flow Start. np:%u at
%u\n",np,*(&t_run));fflush( stdout);}

    if(!udp && (flow[i].state & ATTACK)){ // if TCP - check addition points for
half-open attack
        list = 1 ;
        for( j = 0 ; j <= 1 ; j++ ) {
            k = 1 - j ;
            if(( flow[i].pkts[j] > 16 ) && ( flow[i].flag[j][SYN] >
(0.75 * flow[i].pkts[j] ) ) &&
                                flow[i].flag[k][S_A] ) { //
if half-open attack, 'j' attacking 'k'
                                if(( h[j] ) && ( host[ h[j] ].alerts == HO_ATTACK )
) {
                                    host[ h[j] ].concern += HO_ATK_PER_SYN *
(flow[i].flag[j][SYN] - 12 ) ;
                                } // end - find_host() ok
                            }
                        } // - end - for j = 0,1 and k = 1,0
                    } // end - check for half-open (lots of SYN's evoking SYN-ACK's)

if(flow[i].state & ATTACK ) { list = 1 ; strcat( reason, " Attack") ;}
if(flow[i].state & PROBE ) strcat( reason, " Probe" ) ; // don't set 'list' -too
many probe flows
} // end - end-of-flow analysis

if(clear && (list||f_all||f_demo||(flow[i].state & WATCH_FLOW))) { // == write to
flow-log ==//

    unsigned int ip0, ip1 ;                                // option "a" (f_all == 1) logs
all flows
    unsigned char as0[16], as1[16] ;
    ip0 = flow[i].ip[0] ;
    ip1 = flow[i].ip[1] ;
if( f_verbose == 3) {printf(" List-Flow Start. i:%u at %u\n", i, *(&t_run)) ;
fflush( stdout);}

    n_fprint ++ ; // select flows to log
    n_flow_log ++ ; // cum
// if( f_dotdec ) { // cmd line flag 'd' -
print as dotted-decimal --
sprintf( as0, "%3u.%3u.%3u.%3u", (ip0>>24) & 0xff, (ip0>>16) & 0xff, (ip0>>8) & 0xff,
ip0 & 0xff) ;
sprintf( as1, "%3u.%3u.%3u.%3u", (ip1>>24) & 0xff, (ip1>>16) & 0xff, (ip1>>8) & 0xff,
ip1 & 0xff) ;

    fprintf(log_flow, "%u\t %s\t %s\t %u\t %u\t %u\t %u\t %u\t",
        flow[i].state, as0, as1, flow[i].pt[0], flow[i].pt[1],
flow[i].service, flow[i].start, flow[i].last);
//} else { // print as 8-hex
//    fprintf(log_flow, "%u\t %x\t %x\t %u\t %u\t %u\t %u\t %u\t",
//        flow[i].state, ip0, ip1, flow[i].pt[0], flow[i].pt[1], service,
flow[i].start, flow[i].last);

```


LANcope Code

```
//}

fprintf(log_flow, "%u\t %u\t %x\t %u\t %u\t",
flow[i].bytes[0], flow[i].pkts[0], flow[i].flgs[0], flow[i].pt_min, flow[i].pt_max
);

if( flow[i].bin_norm[0] ) fprintf(log_flow, "%u\t", (25 *
flow[i].binary[0])/flow[i].bin_norm[0]) ;
else fprintf(log_flow, "255\t") ;

fprintf(log_flow, "%u\t%u\t%u\t%u\t%u\t%u\t",
flow[i].flag[0][0], flow[i].flag[0][1], flow[i].flag[0][2], flow[i].flag[0][3] ,
flow[i].flag[0][4], flow[i].flag[0][5], flow[i].flag[0][6] );

fprintf(log_flow, "%u\t %u\t %x\t %u\t %u\t",
flow[i].bytes[1], flow[i].pkts[1], flow[i].flgs[1], flow[i].pt_min, flow[i].pt_max
);

if( flow[i].bin_norm[1] ) fprintf(log_flow, "%u\t", (25 *
flow[i].binary[1])/flow[i].bin_norm[1]) ;
else fprintf(log_flow, "255\t") ;

fprintf(log_flow, "%u\t%u\t%u\t%u\t%u\t%u\t%u\t",
flow[i].flag[1][0], flow[i].flag[1][1], flow[i].flag[1][2], flow[i].flag[1][3],
flow[i].flag[1][4], flow[i].flag[1][5], flow[i].flag[1][6], reason );

} // end of select to fprintf(log_flow, ... )

        if( clear) { // ===== clear flow[i] ===== //
            if( flow[i].up) flow[ flow[i].up ].down = flow[i].down ; // if .up
not zero
            if( flow[ flow[i].down ].up == i) flow[ flow[i].down ].up =
flow[i].up ; // one is true
            if( flow[ flow[i].down ].root == i) flow[ flow[i].down ].root =
flow[i].up ;

            memset( (void *) & flow[i].ip[0] , '\0', (size_t) ( sizeof( struct
flow_db ) ) );
            flow[i].down = 0 ;
            if( flow[i].flag[1][7] != 0) printf("#### #### FLOW SLOT NOT BEING
ZEROED #### ####\n"); ;

            if(n_active > n_active_max) n_active_max = n_active ;
            n_active -- ;
        } // end - clear flow

if( f_verbose == 3) {printf(" Flow_class 1 flow %u done. np:%u at %u\n", i, np,
t_run) ; fflush( stdout);}
        } // end of confirming (.down == 0)
pthread_mutex_unlock( &mp_flows) ; // ### unblock process_pkts
    } // end of (.down == 0) && remove flow
    } // end i = 1 to SLOTS

    if(f_verbose) {
        fflush( log_flow ) ;
        printf(" t_run (s): %u, next web: %u, Flows lost: %u, Flows
Ended: %u, Flows Listed: %u\n",
            *(&t_run), t_next_web - t_zero, n_full, flows_ended,
n_fprint) ;
    }
    if(( t_here >= t_next_web) && (running != 2)) {
        Page 44
    }

```

```

                                LANcope Code
                                t_next_web += WEB_ALERT_INT ;
                                web_alerts( ) ;                                // #####          #####          call
web_alerts
    }
    if(( t_here >= t_next_prof) && (running != 2)) {
        t_next_prof += WEB_ALERT_INT ;
        save_profiles( ) ;                                // #####          #####          call
save_profiles
    }
    this_hour =( (t_here / 3600) % 24 ) ; // hour of the day, 1 - 23
    if( last_hour > 23 ) last_hour = this_hour ;

if(f_verbose >= 2) printf(" Restart_hour: %d Last_hour: %d Day: %d, this_hour: %d,
minutes : %d\n",
restart_hour, last_hour, ((t_here / 86400) % 30), this_hour, (t_here / 60) % 60 ) ;

    if( (this_hour == restart_hour) && (last_hour != restart_hour) ) {
        i = save_profiles() ;
        printf("\n ##### Good Bye. Saved %u Profiles for Tomorrow.
#####\n\n", i ) ;
        suicide( (t_here / 86400) % 30 ) ; // parameter is day 0-29, name
of log directory
    }
    last_hour = this_hour ; // for next check

    if( f_file) {
        if( f_verbose >= 2 ) printf(" Classify_Flows about to sleep. t_run
:%u\n", *(&t_run) ) ;
        pthread_mutex_unlock( &mp_class_flow) ; // ### unblock process_pkts
        sleep(1) ;
    }
    if( running == 2) break ; // run once to finish up

if( f_verbose == 3) {printf(" Flow-Class Bottom. np:%u at %u\n", np, t_run) ;
fflush( stdout);}
} // ===== end while(running)

if(f_verbose) {
    printf("* Thread class_flow finishing at t: %u, np: %u\n",t_here - t_zero, np);
    fflush( log_flow ) ; fflush( stdout ) ;
}
return ;
} // end class_flow()

// ### SCAN_PAIR - KEEP STATISTICS BASED ON PROBER-TARGET IP ADDRESSES

unsigned long scan_pair(unsigned long ip0, unsigned long ip1, unsigned char type,
unsigned short port)
{ // type: 0 - empty, 1 - UDP, 2 - TCP, 8 - S-addr==D-addr
    unsigned long x, i, i_mark, n, index, scans_size = SCAN_SLOTS, min_type,
min_slot ;
    size_t t_here ;

    if( f_verbose == 3) {printf(" Scan_Pair Start. np:%u at %u\n", np,
*(&t_run)) ; fflush( stdout);}
    x = ip0 ^ (ip1 << 6) ^ (ip1 >> 26) ;/*** make index from DA, SA, port
***/
    index = x ;
    for (i = SCAN_SHIFT ; i < 32 ; i += SCAN_SHIFT ) {
        x = x >> SCAN_SHIFT ;
        index ^= x ; // XOR bytes together
    }

```

```

                                LANcope Code
index = index & SCAN_MASK ; // limit to right SCAN_SHIFT bits
index++ ; // index can be 1 to 2^n +1

if( f_verbose > 1) printf("###scan_pair, np:%u, index: %u, type: %u, port: %u", np,
index, type, port ) ;
t_here = *(&t_run) + *(&z_sec) ;

// --- look for matching connection or first empty slot
if( scans[index].root) { // root not empty, run through list, look for
matching scan
do {
i = scans[index].root ;
if((scans[i].ip0 != ip0) || (scans[i].ip1 != ip1)) {
if( (scans[i].up)) {
i = scans[i].up;
} else {
break ; // break out of while(1) - end of
list, no match
}
} else { // slot for scan already exists
goto update_pair ;
}
} while( 1) ; // break out when end of list or match found
i_mark = i ; // index of last entry in list - NEW HOST ENTRY
for( n = 0 ; n < SCAN_RANGE ; n++) {
i += 5 + n ;
if( i >= SCAN_SLOTS ) i = i - SCAN_SLOTS + 1; // can not
use i = 0
if(scans[i].down == 0 ) { // empty, use for new entry
scans[i_mark].up = i ;
scans[i].down = i_mark ;
goto new_pair ;
}
}
return( 0 ) ; // scan data sub-structure full
}
else { // scans[index].root == 0, search for any empty slot for NEW
ENTRY
i = index ;
for( n = 0 ; n < SCAN_RANGE ; n++) {
i += 5 + n ;
if( i >= SCAN_SLOTS ) i = i - SCAN_SLOTS + 1; // can not
use i = 0
if(scans[i].down == 0 ) {
scans[index].root = i ;
scans[i].down = index ;
goto new_pair ; //
}
}
return( 0 ) ; // scan data sub-structure full
}
new_pair:
n_scans++ ;
// if( n > n_pr_search) n_pr_search = n ; // check hash efficiency
scans[i].up = 0 ;
scans[i].ip0 = ip0 ;
scans[i].ip1 = ip1 ;
scans[i].start = scans[i].last = *(&t_run) + t_zero ;
scans[i].port[0] = port ;

```

LANcope Code

```

scans[i].type[0] = type ;
scans[i].n_hits = 1 ;
scans[i].n_ports = 1 ;
scans[i].concern = 100 ;
if(type > 8) scans[i].concern += 200 << (type - 8) ; // 9,10,11,12 ->
200,400,800,1600

if( f_verbose > 1) printf("  new-pair, i:%u type: %d, port%d, concern: %u\n",
i, (int) type, (int) port, scans[i].concern ) ;

return( i ) ;

update_pair:
min_type = 100 ;
scans[i].last = *(&t_run) + t_zero ;
scans[i].n_hits ++ ;
if( scans[i].n_ports < 16 ) {
    for(n = 0 ; n < 16 ; n++ ) { // fill a new slot or find a match
        if( scans[i].type[n] < min_type ) {
            min_type = scans[i].type[n] ;
            min_slot = n ;
        }
        if( scans[i].type[n] == 0 ) {
            scans[i].port[n] = port ;
            scans[i].type[n] = type ;
            scans[i].n_ports = n + 1 ;
            break ;
        }
        if(scans[i].type[n]==type) {
            if (scans[i].port[n] == port) { // already present
                if( scans[i].walk[n] < 0xff)
                    scans[i].walk[n] ++ ;
                break ;
            }
            if((port > 1023) && (port < (scans[i].port[n]+5)))
                &&(scans[i].walk[n]<255)){
                    scans[i].port[n] = port ; // port walking
                    if( scans[i].walk[n] < 0xff)
                        scans[i].walk[n] ++ ;
                    break ;
                }
        }
    }
    // breaks go here
    if( (n == 16) && (type > 6)) {
        if( type == scans[i].type[ min_slot ] ) {
            scans[i].port[ min_slot ] = port ;
        }
        else {
            if( type > scans[i].type[ min_slot ] ) {
                scans[i].port[ min_slot ] = port ;
                scans[i].type[ min_slot ] = type ;
            }
        }
    }

    scans[i].concern += 100 ;
    if(type > 8) scans[i].concern += 200 << (type - 8) ; // 9,10,11,12 ->
    200,400,800,1600

    if( f_verbose > 1) printf("  update-pair, i:%u, pair hits: %u, slots
filled: %u, concern: %u\n",
i, scans[i].n_hits, scans[i].n_ports, scans[i].concern) ;
    if( f_verbose == 3) {printf(" Scan_Pair End. np:%u at %u\n", np,

```

LANcope Code

```

*(&t_run)) ; fflush( stdout);}

```

```

return( i ) ;
} // end of scan_pair

```

```

unsigned long find_host( unsigned long ip, unsigned int make)
{
    // returns host[i] unsigned Index, HOSTS MUST BE LOCKED
    unsigned long x, i, i_mark, n, index, scans_size = HOST_SLOTS, unlock = 0 ;

    x = ip ^ (ip << 6) ; /* make index from ip */
    index = x ;
    for (i = HOST_SHIFT ; i < 32 ; i += HOST_SHIFT) {
        x = x >> HOST_SHIFT ;
        index ^= x ; // XOR bytes together
    }
    index = index & HOST_MASK ; // limit to right HOST_SHIFT bits
    index++ ; // index can be 1 to 2^n +1

    if( ! pthread_mutex_trylock( &mp_hosts ) ) { // this will lock mutex if not
locked already
printf( " ### find_host() without mutex m_host being set. t: %u, Running:
%u\n", *(&t_run), running);
        unlock = 1 ;
    }
#ifdef CHECK_INDEX
    if ( index >= HOST_SLOTS ) {
        printf("index bigger than HOST_SLOTS (%u > %u) at record %u\n",
index, HOST_SLOTS, *(&np));
        exit(-1) ;
    }
#endif
    // --- look for matching HOST or first empty slot

    if( host[index].root ) { // root not empty, run through list, look for
matching scan
        i = host[index].root ;
        do {
            if( host[i].ip != ip ) {
                if( host[i].up ) {
                    i = host[i].up ; // loop again
                } else {
                    break ; // break out of while(1) - end of
list, no match
                }
            } else {
                host[i].last = *(&t_run) + t_zero ; // this is
"update_host:"
                if( unlock ) pthread_mutex_unlock( &mp_hosts) ; // ### unlock hosts[]
                return( i ) ; // slot for scan already exists
            }
        } while( 1) ; // break out when end of list, match found ->
return

        i_mark = i ; // index of last entry in list - NEW HOST ENTRY
        if( make == 0 ) return( 0 ) ; // !make -> do not make a new host
entry

        for( n = 0 ; n < HOST_RANGE ; n++) {
            i += 5 + n ;

```

```

                                LANcope Code
                                if( i >= HOST_SLOTS ) i = i - HOST_SLOTS + 1;    // can not
use i = 0
                                if(host[i].down == 0 ) {    // empty, use for new entry
                                    host[i_mark].up = i ;
                                    host[i].down = i_mark ;

                                    goto new_host ;
                                }
                                }
                                printf("H") ;
if( unlock ) pthread_mutex_unlock( &mp_hosts) ;    // ### unlock hosts[]
                                return( 0 ) ;    // Host data sub-structure full
                                }

ENTRY    else {    // host[index].root == 0, search for any empty slot for NEW
entry
                                if( make == 0 ) return( 0 ) ;    // !make -> do not make a new host

                                i = index ;
                                for( n = 0 ; n < HOST_RANGE ; n++) {
                                    i += 5 + n ;
                                    if( i >= HOST_SLOTS ) i = i - HOST_SLOTS + 1;    // can not
use i = 0
                                    if(host[i].down == 0 ) {
                                        host[index].root = i ;
                                        host[i].down = index ;
                                        goto new_host ;
                                    }
                                }
                                printf("H") ;
if( unlock ) pthread_mutex_unlock( &mp_hosts) ;    // ### unlock hosts[]
                                return( 0 ) ;    // Host data sub-structure full
                                }

new_host:
                                host[i].up    = 0 ;
                                host[i].ip = ip ;
                                host[i].start = host[i].last = (&t_run) + t_zero ;
                                for ( n = 0 ; n < ln_max ; n++) {
                                    if( ! ( local_mask[ n ] & ( local_net[ n ] ^ ip ))) {
                                        host[i].alerts |= LOCAL_HOST ;    // set local-host bit
                                        active_locals++ ;
                                        break ;
                                    }
                                }
                                n_host++ ;
                                if( n > n_pr_search) n_pr_search = n ;    // check hash efficiency
                                return( i ) ;
if( unlock ) pthread_mutex_unlock( &mp_hosts) ;    // ### unlock hosts[]
} // end of find_host()

void    print_host(FILE *xfile, unsigned long h, unsigned long v)    // NOT PRESENTLY
USED
{
    unsigned long j, ip, n, x, a0, a1, a2, a3 ;
    char as0[16] ;
    ip = host[h].ip ;
sprintf( as0, "%3u.%3u.%3u.%3u", (ip>>24) & 0xff, (ip>>16) & 0xff, (ip>>8) & 0xff, ip
& 0xff) ;
    for( j = 0 ; j < strlen(as0) ; j++ ) if( as0[j] == ' ') as0[j] = '0' ;

    a1 = 64 * host[h].pt_scans ;    // MUST MATCH CALCULATION IN 'web_alerts()'

```

```

                                LANcope Code
    if( host[h].alerts & PORT_SCAN2 ) a1 += 400 ;
    if( host[h].alerts & PT_SCAN_ALERT ) a1 += 400 ;
    if( host[h].alerts & HI_HI_CS ) a1 += 200 ;
    if( host[h].alerts & LO_HI_CS ) a1 += 800 ;
    if( host[h].alerts & LO_LO_CS ) a1 += 200 ;
    a2 = 8 * host[h].no_con_t + 8 * host[h].rejects + 1 * host[h].pings + 4 *
host[h].traces
                                + 8 * host[h].bad_pkts + 8 * host[h].bad_flow + 8
* host[h].u_flows;
    a3 = 0 ;                                // application related
//    if( host[h].server & IRC ) a3 += 200 ;
//    if( host[h].client & IRC ) a3 += 100 ;
    a0 = a1 + a2 + a3 ;

fprintf(xfile, " %u\t%u\t%u\t%u\t%s\t %u\t %u\t", a0, a1, a2, a3, as0,
host[h].start, host[h].last) ;
fprintf(xfile, " %u\t %u\t", host[h].bytes_in, host[h].bytes_ot) ;
fprintf(xfile, " %u\t %u\t %u\t %u\t", host[h].pkts_in, host[h].pkts_ot,
host[h].port_smin, host[h].port_smax);
fprintf(xfile, " %u\t %u\t %x\t", host[h].port_cmin, host[h].port_cmax,
host[h].server );
fprintf(xfile, " %x\t %x\t %u\t %u\t", host[h].client, host[h].alerts,
host[h].pt_scans, host[h].resets );
fprintf(xfile, " %u\t %u\t %u\t", host[h].rejects, host[h].no_con_t,
host[h].dns_flows);
fprintf(xfile, " %u\t %u\t %u\t %u\t", host[h].udp_bytes, host[h].mm_s,
host[h].mm_c, host[h].mm_p);
fprintf(xfile, " %u\t %u\t %u\t", host[h].s_flows, host[h].c_flows, host[h].u_flows
);
fprintf(xfile, " %u\t %u\t %u\t %u\t", host[h].pt_scans, host[h].bad_pkts,
host[h].pings, host[h].traces);

fprintf(xfile, "s: ");
    x = host[h].server ; n = 0 ;
    while(( x > 0) && (n < pn_max)) {
        if( x & 1) fprintf(xfile,"%s ", port_name[ n ] ) ;
        n++ ; x = x >> 1 ;
    }
fprintf(xfile, "- c: ");
    x = host[h].client ; n = 0 ;
    while(( x > 0) && (n < pn_max)) {
        if( x & 1) fprintf(xfile,"%s ", port_name[ n ] ) ;
        n++ ; x = x >> 1 ;
    }
    fprintf(xfile, "\n") ;
} // end of print_host()

```

```

unsigned long dots_int( char * p ) { // dotted-decimal to integer

```

```

    unsigned int v, j, ipv ;
    char *sp1, *sp2, buf[120] ;

    strcpy(buf, p) ;
    buf[15] = 0 ;
    v = 0 ;
    j = 0 ;
    sp1 = sp2 = buf ; // beginning of string "149.77.8.2"
    while (j< 5) {
        j++ ;
        sp2 = strstr(sp1, ".") ;

```

```

                                LANcope Code
if(sp2) {                                // there's a dot
    sp2[0] = 0 ;                                // sp1 -> "177"
    v = v * 256 + atoi( sp1 ) ;
    sp1 = &sp2[1] ;                                // sp1 -> "77.8.2"
} else {
    ipv = v*256 + atoi( sp1 ) ; // sp1 -> "2"
    break ; // out of while loop
}
if( (atoi(sp1) > 255) || (atoi(sp1) < 0 ) ) j = 10 ; // -> error,
below
    }
    if( j != 4 ) {
        printf(" Can not parse IP: '%s', Quitting\n", p ) ;
        usage() ;
    }
    return( ipv ) ;
} // end of dots_int()

void web_alerts( void ) { // ==== run every 1200 s, only lock hosts
    char *sp, s1[20], s2[400], s3[400], s4[100], web_ts[64], wts[128], ts[16] ;
    FILE *web_alt0, *web_alt1, *web_traf0, *web_traf1, *web_hosts, *web_info,
    *lc_th_file, *web_alarms;
    FILE *web_scans ;
    unsigned int h, i, j, n, n0=0, n1=0, n2=0, n3=0, nh=0, nf=0, n_scan_prt,
n_host_drop, drop_hosts ;
    unsigned int x, a, a0, a1, a2, a3, pu, file_fail, error_count, odd_bit, traf
;
    time_t      t_1, t_2, t_here, t_tab, t_cut ;
    struct tm    *w_time ;
    int m, local, dst ;

    if( f_verbose) printf(" 'web_alert' started at t_run: %u s, pkts: %u\n",
*(&t_run), np) ;
    if( f_verbose > 1 ) fflush( stdout ) ;
    if( *(&t_run) > LOOSE_PERIOD ) f_loose = f_splitpath ; // continue loose
classify if split_path
    odd_bit = port_mask[ 2 * UDP_PORT_OFFSET + 4] ; // bit for odd service,
psedo-port = 2052

    if( f_file) t_here = *(&t_run) + t_zero ;
    else t_here = time( NULL ) ; // real time

pthread_mutex_lock( &mp_bs) ; // ### lock bs[]
    if( t_here > (t_bs_last + TRAF_TABLE_MIN ) ) {
        bt ++ ; // bs[ bt + 1 ] may not be reliable in another thread, also
bt may be > TRAFFIC_VALUES
        if( bt == TRAFFIC_VALUES ) bt = 0 ;
        bs[ bt ].bytes_in = bs[ bt ].bytes_out = bs[ bt ].bytes_loc = bs[ bt
].bytes_oo = 0 ;
        memset( (void *) &bs[ bt ] , '\0', (size_t) ( sizeof( struct
byte_table ) ) ) ;
        t_bs_last = t_here - 1 ;
    }

    bs[ bt ].t = t_here ;
    bs[ bt ].bytes_in += bytes_in_cnt ;
    bs[ bt ].bytes_out += bytes_out_cnt ;
    bs[ bt ].bytes_loc += bytes_loc_cnt ;
    bs[ bt ].bytes_oo += bytes_oo_cnt ; //-----> Record Traffic
Load for web Table
    bs[ bt ].bytes_bc += bytes_bc_cnt ;

```



```

                                LANcope Code
bs[ bt ].bytes_mcn += bytes_mcn_cnt ;
bs[ bt ].bytes_mco += bytes_mco_cnt ;
bs[ bt ].bytes_bad += bytes_bad_cnt ;

].bytes_in ;      if(bs[ bt ].bytes_in > bps_in_max ) bps_in_max = bs[ bt
].bytes_out ;      if(bs[ bt ].bytes_out > bps_out_max) bps_out_max = bs[ bt
].bytes_loc ;      if(bs[ bt ].bytes_loc > bps_oo_max ) bps_oo_max = bs[ bt
].bytes_oo ;      if(bs[ bt ].bytes_oo > bps_loc_max) bps_loc_max = bs[ bt
].bytes_mcn ;      if(bs[ bt ].bytes_mcn > bps_mcn_max) bps_mcn_max = bs[ bt
].bytes_mco ;      if(bs[ bt ].bytes_mco > bps_mco_max) bps_mco_max = bs[ bt
].bytes_bc ;      if(bs[ bt ].bytes_bc > bps_bc_max ) bps_bc_max = bs[ bt
].bytes_bad ;      if(bs[ bt ].bytes_bad > bps_bad_max) bps_bad_max = bs[ bt

bytes_in_cnt = bytes_out_cnt = bytes_loc_cnt = bytes_oo_cnt = 0 ;
bytes_mcn_cnt = bytes_mco_cnt = bytes_bc_cnt = bytes_bad_cnt = 0 ;

pthread_mutex_unlock( &mp_bs) ; // ### unlock bs[]

//if(f_file) {
//    t_next_web = WEB_ALERT_INT ; // left over from when this was a separate
//    thread
//}
//else {
//    unsigned int wai = WEB_ALERT_INT ;
//    t_next_web = t_zero + 0.5 * wai ;
//    t_next_web = t_next_web + wai - (t_next_web % wai) + 1 ; // moves to nearest
//    even value +1
//} // so new value traffic graph will complete before this runs

//while( running)
//    sleep( 10) ; // in case a file problem causes a "continue"

//    while(( t_here < t_next_web) && (running == 1)) {
//        if( f_file) t_here = *(&t_run) ;
//        else t_here = time( NULL ) ;
//        sleep(10) ; // check time and 'running' every 10 seconds
//    }

    if( running == 0 ) return ; // break ;
    t_1 = t_here ;
    t_2 = time( NULL ) ;
    w_time = localtime( &t_1) ;
    dst = w_time->tm_isdst ; // >0 if daylight savings time
    alarm_lines = 0 ;
pthread_mutex_unlock( &mp_bs) ; // ### lock hosts[]

pthread_mutex_lock( &mp_hosts) ; // ### unlock bs[]
    read_thresholds( ) ; // update thresholds from file lc_thresholds.txt
pthread_mutex_unlock( &mp_hosts) ; // ### unlock hosts[]

strcpy( web_ts, "web Prepared: " ) ;
strcat( web_ts, asctime( w_time )) ;
web_ts[ 38 ] = 0 ; // delete \n from asctime()
strcpy( wts, monitor_start ) ;

```

LANcope Code

```

        strcat( wts, web_ts );
if(f_verbose) { printf("* web_alert operating at t: %u, np: %u, %s\n", t_here -
t_zero, np, web_ts);
fflush( stdout); }

// ===== START OF PROBE TABLE =====//

        if( (web_scans = fopen("web_scans.txt","w")) ==NULL) { // -----OPEN
OUTPUT FILE web_scans.txt
        printf("\nLog-Scans File 'web_scans.txt' Can Not Be Opened\n\n");
        }
        else { // file 'web_scans' opened OK

        register int i, j, n ;
        n_scan_prt = 0 ;
        for( i = 0 ; i < 15 ; i++ ) scin[ i ] = 0 ;

if( f_verbose == 2 ) {printf(" --- Scan-Pairs about to begin.\n"); fflush( stdout )
; }

        for( i = 1 ; i < SCAN_SLOTS ; i++ ) { // ### WRITE SCAN-PAIRS ###
                register unsigned int ip0, ip1;
                char as0[20], as1[20], as[30], as4[30], pr_str[500], x_str[50] ;
                if( scans[i].down) { // select pairs to fprint
                        register int j, k, tf, done ;
                        int delete_pair = 0, display_pair = 0 ;

pthread_mutex_lock( &mp_pairs) ; // ### lock scans[],
                if( ( scans[i].last + 1200 ) > t_here ) tf = scans[i].last +
1200 - t_here ; // time factor for display
                else tf = 0 ;

                if(((scans[i].concern + tf ) < scans_cut )) {
                        delete_pair = 1 ;
                }
                else {
                        for( k = 1 ; k < 15 ; k++ ) { // put scans with
values of concern into bins
                                if( ( scans[i].concern + tf ) < cix[k]) {
                                        scin[k]++ ;
                                        break ;
                                }
                        }
                } // end - not cut

                if(((scans[i].concern + tf ) > scans_pr_cut )) display_pair
= 1 ;

                if( f_verbose == 2 ) printf(" scans_cut: %u, scans_pr_cut %u,
scans[%u].concern: %u\n",
                scans_cut, scans_pr_cut, i, scans[i].concern ) ;

                if( delete_pair || display_pair ) {
                        ip0 = scans[i].ip0 ;
                        ip1 = scans[i].ip1 ;
                        sprintf( as0, "%3u.%3u.%3u.%3u", (ip0>>24) & 0xff, (ip0>>16) & 0xff, (ip0>>8)
& 0xff, ip0 & 0xff) ;
                        sprintf( as1, "%3u.%3u.%3u.%3u", (ip1>>24) & 0xff, (ip1>>16) & 0xff, (ip1>>8)
& 0xff, ip1 & 0xff) ;
                        for( j = 0 ; j < strlen(as0) ; j++ ) if( as0[j] == '
') as0[j] = '0' ; // target ip0
                        for( j = 0 ; j < strlen(as1) ; j++ ) if( as1[j] == '

```

LANcope Code

```

') as1[j] = '0' ; // prober ip1
        sprintf(pr_str, "%u\t%u\t%s\t%s\t%u\t%u\t", scans[i].last,
scans[i].start, as0, as1,
        scans[i].n_hits, scans[i].n_ports );
        for( j = 0 ; j < 16 ; j++ ) {
            x_str[0] = 0 ; done = 0 ;
            switch ( scans[i].type[j] ) {
                case 1: sprintf(x_str, "UDP_R-%u", scans[i].port[j]) ;break ; //
UDP_PROBE
                case 2: sprintf(x_str, "TCP_R-%u", scans[i].port[j]) ;break ; //
TCP_PROBE
                case 3: sprintf(x_str, "Short_UDP-%u" , scans[i].port[j]) ;break ; //
SHORT_UDP_SCAN
                case 4: sprintf(x_str, "Src=Des-%u", scans[i].port[j]) ;break ; //
BOOMERANG
                case 5: sprintf(x_str, "Ping") ;break ; //
PING_SCAN
                case 6: sprintf(x_str, "ICMP_TO" ) ;break ; //
ICMP_TO
                case 7: sprintf(x_str, "TCP_TO-%u", scans[i].port[j]) ;break ; //
TCP_TO
                case 8: sprintf(x_str, "UDP_TO-%u", scans[i].port[j]) ;break ; //
UDP_TO
                case 9: sprintf(x_str, "Bad_TCP-%u", scans[i].port[j]) ;break ; //
BAD_PKT_TRACE
                case 10: sprintf(x_str, "Multi_Pt-%u", scans[i].port[j]) ;break ; //
TCP_PORT_SCAN
                case 11: sprintf(x_str, "Addr_Scan-%u", scans[i].port[j]) ;break ; //
TCP_ADDR_SCAN
                case 12: sprintf(x_str, "HO_ATTACKn-%u", scans[i].port[j]) ;break ; //
HALF_OPEN
                default : done = 1 ;
            }
            if( done ) break ;
            strcat( pr_str, x_str ) ;
            if( scans[i].walk[j] > 0 ) {
                sprintf(x_str, "(%u) ", scans[i].walk[j] )
;
                strcat( pr_str, x_str ) ;
            }
            else strcat(pr_str, " " ) ;
        } // end j = 0, 1, 2, ...
        strcat(pr_str, "\n") ;
    }
    if( delete_pair ) { // if( delete_pair ) // ===== clear
scan[i] =====//
        fprintf(log_pair, "%u\t%s", scans[i].concern, pr_str) ; //
write to log before deleting
        if( scans[i].up ) scans[ scans[i].up ].down = scans[i].down ; // if .up
not zero
        if( scans[ scans[i].down ].up == i ) scans[ scans[i].down ].up =
scans[i].up ; // one is true
        if( scans[ scans[i].down ].root == i ) scans[ scans[i].down ].root =
scans[i].up ;

        memset( (void *) & scans[i].ip0 , '\0', (size_t) (
sizeof( struct ip_pair ) ) );
        n_scans -- ;
    }
    pthread_mutex_unlock( &mp_pairs) ; // ### unlock scans[],

```

```

                                LANcope Code
                                if(display_pair) {
pr_str) ; // sort on concern + tf      fprintf(web_scans,"%10u\t%s", scans[i].concern + tf,
                                n_scan_prt ++ ;
                                }
                                } // end for i
                                fclose ( web_scans ) ;
} // end - if fopen web_alerts.txt

if( f_verbose == 2 ) {
    printf(" --- Scan-Pairs done. Display: %d, Show > %d, Delete< %d\n",
        n_scan_prt, scans_pr_cut, scans_cut);
    fflush( stdout ) ;
}

// ===== END OF PROBE TABLE =====//

t_diff = t_here - t_wa_last ; // for web_alert bps cal
t_wa_last = t_here ;
if(t_diff < 100) t_diff = 100 ; // may be small at first and when running
== 2

web_traf_2byte = (web_traf_2 * t_diff) >> 3 ; // *dt/8

if((web_info = fopen ("web_info.txt","wb"))==NULL) { // OPEN web_info
FILE      printf("File 'web_info.txt' Can Not Be Opened to Write, t: %u\n", *
(&t_run)) ;
        file_fail = 1 ; goto close_files ;
    }

    if((web_alt0 = fopen ("web_alerts0.txt","wb"))==NULL) { // OPEN
web_alerts0 FILE      printf("File 'web_alerts0.txt' Can Not Be Opened to Write, t: %u\n",
* (&t_run)) ;
        file_fail = 2 ; goto close_files ;
    }

    if((web_alt1 = fopen ("web_alerts1.txt","wb"))==NULL) { // OPEN
web_alerts1 FILE      printf("File 'web_alerts1.txt' Can Not Be Opened to Write, t: %u\n",
* (&t_run)) ;
        file_fail = 3 ; goto close_files ;
    }

    if((web_traf0 = fopen ("web_traf0.txt","wb"))==NULL) { // OPEN web_traf0
FILE      printf("File 'web_traf0.txt' Can Not Be Opened to Write, t: %u\n",*
(&t_run)) ;
        file_fail = 4 ; goto close_files ;
    }

    if((web_traf1 = fopen ("web_traf1.txt","wb"))==NULL) { // OPEN web_traf1
FILE      printf("File 'web_traf1.txt' Can Not Be Opened to Write, t: %u\n",*
(&t_run)) ;
        file_fail = 5 ; goto close_files ;
    }

    if((web_hosts = fopen ("web_hosts.txt","wb"))==NULL) { // OPEN web_hosts
FILE

```



```

LANcope Code
UDP\tServers\tClients\tAlerts\n");

    fprintf(web_traf0,"4294967295\tLocal Hosts with Recent High
Traffic\t%s\t%u\t%u\t%u\n",
        wts, *(&web_traf_2), t_diff, running);
    fprintf(web_traf0,"4294967294\tTotal\tBit/s-In\tBit/s-Out\t\t% UDP\tHost
IP\tConcern\tServers\tClients\tAlerts\n");

    fprintf(web_traf1,"4294967295\tOutside Hosts with Recent High
Traffic\t%s\t%u\t%u\t%u\n",
        wts, *(&web_traf_2), t_diff, running);
    fprintf(web_traf1,"4294967294\tTotal\tBit/s-In\tBit/s-Out\t\t% UDP\tHost
IP\tConcern\tServers\tClients\tAlerts\n");

    memset( (void *) cin , '\0', (size_t) ( 30 * sizeof( long ) ) ); // clear
cin[ ]
    memset( (void *) tin , '\0', (size_t) ( 30 * sizeof( long ) ) );

    n_host_drop = 0 ;
    drop_hosts = ( n_host > HOST_LIMIT ) ; // TRUE if too many hosts in database
    if( f_file ) t_cut = t_here - 200 ; else t_cut = t_here - 1800 ; // do not
drop newbies

//      memset( (void *) temp, '\0' , (size_t) (128 * sizeof( long)) ) ; // DeBuG
    for( h = 1 ; h < HOST_SLOTS ; h++ ) {
        if(host[h].down) { // select hosts to fprint
pthread_mutex_lock( &mp_hosts) ; // ### lock hosts[]

        if( host[h].down ) { // select hosts to fprint - confirm after lock
            register int list_ci, list_traf ;

if( f_verbose == 2 ) {printf(" --- New Host. h:%u, ip: %8x\n", h, host[h].ip) ;
fflush( stdout ) ; }
            list_ci = list_traf = 0 ;

            a1 = host[h].concern ; // ===== Calculate Concern
Index (CI = a0) ===== //

            a2 = 8 * host[h].no_con_t + 8 * host[h].rejects ; // treat pings
and traces as probes
            a3 = 0 ; // application related
            if( host[h].server & IRC ) a3 += 200 ;
            if( host[h].client & IRC ) a3 += 100 ;
            a0 = a1 + a2 + a3 ; // this is the CI
// ###

### ALARMS 2 and 3 SET HERE ### ###
            traf = host[h].bytes_in_pp + host[h].bytes_ot_pp ;
            local = host[h].alerts & LOCAL_HOST ;

            if( a0 > web_alert_2 ) { // if CI greater than limit from
lc_thresholds.txt
                list_ci = 1 ; // list even if alarm shut off
                if( ! ( host[h].alerts & NO_ALARM ) ) { // if alarms not
shut off
                    host[h].alerts |= ALARM_2 ; // set bit, cause email
to NetAdmin
                    host[h].alarm_t = t_here ; // mark time to avoid
too-frequent alerts

```

```

                                LANcope Code
                                }
                                else host[h].alerts &= (~ALARM_2) ; // alarm shut off, if
on
                                }
increased
                                else host[h].alerts &= (~ALARM_2) ; // clear ALARM_2 if web_alert_2

                                if( traf >= web_traf_2byte ) {
                                    host[h].alerts |= TRAF_ALARM ; // send email to Net Admin
                                    host[h].alarm_t = t_here;
                                    list_traf = 1 ;
                                }
                                else host[h].alerts &= (~TRAF_ALARM) ; // clear TRAF_ALARM if
web_traf_2byte increased

                                host[h].port_scan[0] = host[h].port_scan[1] = 0 ; // clear
short-term port scan
                                host[h].scan_cntr[2] = 0 ;

if( f_verbose == 2 ) {printf(" --- Alarms Set or Cleared.  traf: %u\n", traf) ;
fflush( stdout ) ; }

                                if( local ) { // local host lists
ALARM_12) || f_demo ) list_ci if( (a0 >= web_alert0_0) || (host[h].alerts &
                                = 1 ;
                                if( (traf >= web_traf0_0) || f_demo )
                                    list_traf = 1 ;
                                }
                                else {
// outside host lists
ALARM_12) || f_demo ) list_ci if( (a0 >= web_alert1_0) || (host[h].alerts &
                                = 1 ;
                                if( (traf > web_traf1_0) || f_demo )
                                    list_traf = 1 ;
                                }

                                for( i = 1 ; i < 15 ; i++ ) { // put hosts with values of a0 into
bins to set web_alert_0
                                    if( a0 < cix[i] ) {
                                        cin[!local][i]++ ;
                                        break ;
                                    }
                                }

                                for( i = 1 ; i < 15 ; i++ ) { // put hosts with values of traf into
bins to set web_traf_0
                                    if( traf < tix[i] ) {
                                        tin[!local][i]++ ;
                                        break ;
                                    }
                                }

if( f_verbose == 2 ) {printf(" --- Going to calculate UDP\n") ; fflush( stdout ) ; }

                                if( host[h].bytes_in_mx < host[h].bytes_in_pp) host[h].bytes_in_mx =
host[h].bytes_in_pp ;
                                if( host[h].bytes_ot_mx < host[h].bytes_ot_pp) host[h].bytes_ot_mx =
host[h].bytes_ot_pp ;

                                if( host[h].bytes_in + host[h].bytes_ot ) {
overflow
                                    if( host[h].udp_bytes > 42000000 ) { // 100 * will cause

```

```

LANcope Code
8)))/((host[h].bytes_in + host[h].bytes_ot)>>8+1); // %UDP
} else {
    pu = (100 * host[h].udp_bytes)/( host[h].bytes_in
+ host[h].bytes_ot + 1); // %UDP
} else {
    if( host[h].udp_bytes) pu = 100 ; else pu = 0 ;
}

a = host[h].ip ;
sprintf( s1, "%3u.%3u.%3u.%3u", a>>24, (a>>16) & 0xff, (a>>8) & 0xff, a &
0xff ) ; // IP ddec
for( j = 0 ; j < strlen(s1) ; j++ ) { if( s1[j] == ' ' ) s1[j] = '0' ; }

if((local)|| (host[h].alerts & ALARM_12) || list_ci || list_traf || f_demo)
{
if( f_verbose == 2 ) {printf(" --- Goint to List\n") ; fflush( stdout ) ; }

PING_ALERT ; if(host[h].pings > 100 ) host[h].alerts |=
TRACE_ALERT ; if(host[h].traces > 100 ) host[h].alerts |=
REJECT_ALERT ; if(host[h].rejects > 50 ) host[h].alerts |=
PKT_ALERT ; if(host[h].bad_pkts > 10 ) host[h].alerts |=
PT_SCAN_ALERT ; if(host[h].pt_scans > 5 ) host[h].alerts |=

x = (host[h].alerts >> 1) ; n = 1 ; sp = s4 ; s4[0]
= 0 ; // s4 - alert list, skip '0' local
while(( x > 0) && (n < max_alert)) {
    if( x & 1) {
        sprintf(sp,"%s ", alert_name[ n ] ) ;
        if( strlen(s4) > 380 ) {
            j = strlen(s4) ;
            s4[ j + 1 ] = 0 ;
            s4[ j ] = '+' ;
            break ;
        }
    }
    sp = & s4[ strlen(s4) ] ;
    n++ ; x = x >> 1 ;
} // end while
}
if( local ) { // local host list
    nh++ ;

x = host[h].server ; s2[0] = 0 ; // server x list
for(n = 0 ; n < pn_max ; n++) {
    if( x & 1) strcat(s2,"\tx" ) ;
    else strcat(s2,"\t " ) ;
    if( strlen( s2 ) > 380 ) break ;
    x = x >> 1 ;
}

x = host[h].client ; s3[0] = 0 ; // client x list
for(n = 0 ; n < pn_max ; n++) {
    if( x & 1) strcat(s3,"\tx" ) ;
    else strcat(s3,"\t " ) ;
    if( strlen( s3 ) > 380 ) break ;
}

```



```

LANcope Code
    x = x >> 1 ;
}

fprintf(web_hosts,"%s\t%u\t%s\t",s1,a0,s4);
fprintf(web_hosts,"%u\t%u\t%u", host[h].bytes_in_mx,
host[h].bytes_ot_mx, pu );
fprintf(web_hosts,"%s%s\n", s2, s3 ) ; // s2 and s3 start
with \t
} // end 'if local'
else nf++ ;

if((host[h].alerts & ALARM_12) || list_ci || list_traf ||
f_demo) {

    x = host[h].server ;
    n = 0 ; sp = s2 ; s2[0] = 0 ; // s2-server list
    while(( x > 0) && (n < pn_max)) {
        if( x & 1) {
            sprintf(sp,"%s ", port_name[ n ] ) ;
            sp = & s2[ strlen(s2) ];
            if( strlen(s2) > 380 ) {
                j = strlen(s2) ;
                s2[ j + 1 ] = '0' ;
                s2[ j ] = '+' ;
                break ;
            }
        }
        n++ ; x = x >> 1 ;
    } // end while

    for(x = 0 ; x < 10 ; x++ ) {
        if(( host[h].s_list[x] == 0) || ( strlen(s2)
> 380 )) break ; // add ports not in bit map
        sprintf(sp,"%u ", host[h].s_list[x] ) ;
        sp = & s2[ strlen(s2) ];
    }

    x = host[h].client ;
    n = 0 ; sp = s3 ; s3[0] = 0 ; // s3 - client list
    while(( x > 0) && (n < pn_max)) {
        if( x & 1) {
            sprintf(sp,"%s ", port_name[ n ] ) ;
            sp = & s3[ strlen(s3) ];
            if( strlen(s3) > 380 ) {
                j = strlen(s3) ;
                s3[ j + 1 ] = '0' ;
                s3[ j ] = '+' ;
                break ;
            }
        }
        n++ ; x = x >> 1 ;
    } // end while

    for(x = 0 ; x < 10 ; x++ ) {
        if(( host[h].c_list[x] == 0) || ( strlen(s3)
> 380 )) break ; // add ports not in bit map
        sprintf(sp,"%u ", host[h].c_list[x] ) ;
        sp = & s3[ strlen(s3) ];
    }

} // end build s2,s3

```

```

                                LANcope Code
        if( local ) { // local host alert list
            if( list_ci ) {
                n0++ ;
fprintf(web_al0,"%u\t%s\t%u\t%u\t%u\t%s\t%s\t%s\n",
a0,s1,host[h].bytes_in, host[h].bytes_ot,pu,s2,s3,s4);
            }
        }
        if(!(local)) { // outside host - concern alert list
            if( list_ci ) {
                n1++ ;
fprintf(web_al1,"%u\t%s\t%u\t%u\t%u\t%s\t%s\t%s\n",
a0,s1,host[h].bytes_in, host[h].bytes_ot,pu,s2,s3,s4);
            }
        }

        if( local ) { // local host traffic
alert list
            if( list_traf ) {
                n2++ ;
fprintf(web_traf0,"%u\t%u\t%u\t%u\t%u\t%s\t%s\t%s\t%s\n", (8*traf)/t_diff, (8*host[h].
bytes_in_mx)/t_diff,
                (8*host[h].bytes_ot_mx)/t_diff,pu,s1,a0,s2,s3,s4) ;
            }
        }
        if(!( local)) { // not a local host -
traffic alert list
            if( list_traf ) {
                n3++ ;
fprintf(web_traf1,"%u\t%u\t%u\t%u\t%u\t%s\t%s\t%s\t%s\n", (8*traf)/t_diff, (8*host[h].
bytes_in_mx)/t_diff,
                (8*host[h].bytes_ot_mx)/t_diff,pu,s1,a0,s2,s3,s4)
;
            }
        } // traffic > x

// ===== ALARMS, OUT OF PROFILE REPORT
=====
        if( host[h].alerts & ALARM_2 ) {
            fprintf( web_alarms, "%u\t%s\tHIGH
CONCERN\t%u\t%u\t%s\n", host[h].alarm_t, s1,a0,traf,s4); // s1=dot-ip
        } // end ALARM_1

        if( host[h].alerts & ALARM_1 ) {
            fprintf( web_alarms,
"%u\t%s\tTouched\t%u\t%u\t%s\n", host[h].alarm_t, s1,a0,traf,s4);
        } // end ALARM_0

        if( host[h].alerts & TRAF_ALARM ) {
            fprintf( web_alarms, "%u\t%s\tHigh
Traffic\t%u\t%u\t%s\n", host[h].alarm_t, s1,a0,traf,s4);
        } // end TRAF_ALARM

if(local) {
    if( profile & 0x10 ) { // profile == 2 or 3, 0=clear every night,
1=save at night, add new
        register unsigned long s, c ; // 2=alarm & no add, 3 alarm and add

```

```

LANcope Code
if( f_verbose == 2 ) {printf(" --- Services vs. Profiles\n") ; fflush( stdout ) ; }

s = (~host[h].server) & host[h].s_profile ;
c = (~host[h].client) & host[h].c_profile ; // test profile
compliance
if( s | c ) {
    alarm_lines ++ ;
    fprintf( web_alarms, "%s - Out of Profile.", s1 ) ;

    if (s ) {
        services( s ) ;
        fprintf( web_alarms, " Server OoP: %s.",
serstr ) ;

        if( c & odd_bit ) {
            for(x = 0 ; x < 10 ; x++ ) {
                if( host[h].s_list[x] == 0)
                    fprintf(web_alarms,"%u ",
break ; // add ports not in bit map
host[h].s_list[x] ) ;
            }
        }
        if (c ) {
            services( c ) ;
            fprintf( web_alarms, " Client OoP: %s.",
serstr ) ;

            if( c & odd_bit ) {
                for(x = 0 ; x < 10 ; x++ ) {
                    if( host[h].c_list[x] == 0)
                        fprintf(web_alarms,"%u ",
break ; // add ports not in bit map
host[h].c_list[x] ) ;
                }
            }
        }
        fprintf( web_alarms, "\n" ) ;
    }

    if( profile & 0x01 ) { // profile == 1 or 3 -> add new bits to
profile
        host[h].s_profile |= host[h].server
;
        host[h].c_profile |= host[h].client
; // auto-build profiles
} // end LOCAL_HOST - Profiles

    if(host[h].bytes_in_pp > host[h].bytes_in_mx)
host[h].bytes_in_mx = host[h].bytes_in_pp ;
    if(host[h].bytes_ot_pp > host[h].bytes_ot_mx)
host[h].bytes_ot_mx = host[h].bytes_ot_pp ;
    host[h].bytes_in_pp = host[h].bytes_ot_pp = 0 ; // zero to
collect bytes for next period

// ==== CLEAR host[h] ==== //

    if( drop_hosts && (!(local)) && (a0 == 0) && ( traf <
host_cut) && (host[h].last < t_cut) ) {

        if( host[h].up )
            host[ host[h].up
].down = host[h].down ; // if .up not zero
}

```

```

                                LANcope Code
                                if( host[ host[h].down ].up == h) host[
host[h].down ].up = host[h].up ; // one is true
                                if( host[ host[h].down ].root == h) host[
host[h].down ].root = host[h].up ;
                                memset( (void *) & host[h].ip , '\0', (size_t) (
sizeof( struct host_db ) ) );
                                n_host -- ; n_host_drop ++ ;
                                }
                                } // .down > 0 confirmed afer lock
                                pthread_mutex_unlock( &mp_hosts) ; // ### unlock hosts[]
                                //if(!((nh+nf)%100)) printf(".");
                                //if(!((nh+nf)%10000)) printf("\n");
                                } // .down > 0
} // end h++
file_fail = 8 ;

close_files:
switch( file_fail ) {
    case 8 :
        fclose( web_alarms ) ; // fall-thru desired (no 'breaks')
    case 7 :
        fclose( web_hosts ) ;
    case 6 :
        fclose( web_traf1 ) ;
    case 5 :
        fclose( web_traf0 ) ;
    case 4 :
        fclose( web_alt1 ) ;
    case 3 :
        fclose( web_alt0 ) ;
    case 2 :
        fclose( web_info ) ;
    case 1 :
    default:
}
if( file_fail < 8 ) printf(" Problem opening a file. close-index: %u\n",
file_fail ) ;
if( f_verbose == 2) {printf(" WA Web files closed. np:%u at %u\n", np, t_run) ;
fflush( stdout);}

// ===== Determine cut-off value for pruning scans[] ===== //
{
int max_slots, max_print, m ;

max_slots = 0.5 * SCAN_SLOTS ;
max_print = 50 ;

    if( n_scans < max_slots) slots_cut = 0 ;
    else {
        m = 0 ;
        for(i = 14 ; i > 0 ; i-- ) {
            m += scin[i] ;
            scans_cut = cix[ i-1 ] ; // set value of slots_cut to
reduce db
            if( m > max_slots ) {
                break ;
            }
        }
    }

    if( n_scans <50) slots_pr_cut = 0 ;
    else {

```

LANcope Code

```

    m = 0 ;
    for(i = 14 ; i > 0 ; i-- ) {
        m += scin[i] ;
        scans_pr_cut = cix[ i-1 ] ;    // set value of slots_pr_cut
to select for web
        if( m > 50 ) {
            break ;
        }
    }
}
if( f_verbose == 2 ) {printf(" --- New scans_cut: %u, scans_pr_cut %u\n\n",
    scans_cut, scans_pr_cut ) ; fflush( stdout ) ; }

{ // ===== Network Statistics ===== //
    register int m ;
    FILE *net_stats ;

    if( nh < LINES_PER_SCREEN ) web_alert0_0 = web_traf0_0 = 0 ;
    else {
        m = 0 ;
        for(i = 14 ; i > 0 ; i-- ) {
            m += cin[0][i] ;
            web_alert0_0 = cix[ i-1 ] ;    // set value of web_alert0_0
            if( m > LINES_PER_SCREEN ) {
                break ;
            }
        }

        m = 0 ;
        for(i = 14 ; i > 0 ; i-- ) {
            m += tin[0][i] ;
            web_traf0_0 = tix[ i-1 ] ;    // set value of web_traf0_0
            if( m > LINES_PER_SCREEN ) {
                break ;
            }
        }
    }

    if( nf < LINES_PER_SCREEN ) web_alert1_0 = web_traf1_0 = 0 ;
    else {
        m = 0 ;
        for(i = 14 ; i > 0 ; i-- ) {
            m += cin[1][i] ;
            web_alert1_0 = cix[ i-1 ] ;    // set value of web_alert1_0
            if( m > LINES_PER_SCREEN ) {
                break ;
            }
        }

        m = 0 ;
        for(i = 14 ; i > 0 ; i-- ) {
            web_traf1_0 = tix[ i-1 ] ;    // set value of web_traf1_0
            m += tin[1][i] ;
            if( m > LINES_PER_SCREEN ) {
                break ;
            }
        }
    }

    if( n_host > HOST_LIMIT ) {
        m = 0 ;
        for(i = 1 ; i < 14 ; i++ ) {
            host_cut = tix[ i+1 ] ;    // set traf value for host_cut
            m += tin[1][i] ;
            if( m > (n_host - HOST_LIMIT) ) {
                break ;
            }
        }
    }
}

```

LANcope Code

```

    }
    }
}

if( f_verbose == 2 ) {printf(" --- Net Stats about to begin.\n") ; fflush( stdout )
; }

    if( (net_stats = fopen("web_stats.txt","wb") )==NULL) { // -----OPEN
OUTPUT FILE web_scans.txt
        printf("\nLog-Scans File 'web_stats.txt' Can Not Be Opened\n\n") ;
    }
    else { // file 'web_stats' opened OK
        for( m = 1 ; m < 15 ; m++ ) {
            fprintf(net_stats,"%u\t%u\t%u\t%u\t%u\t%u\t%u\t%u\n",
                cix[m-1],cix[m],cin[0][m],cin[1][m], tix[m-1],tix[m],tin[0][m],tin[1][m]
) ;
        }
        fclose( net_stats ) ;
    }
if( f_verbose == 2) {printf(" Net-stats done. np:%u at %u\n", np, t_run) ; fflush(
stdout);}
} // end net-stats

// if( running == 2 ) break ; // finish up
// // end - while( running )

if( file_fail == 8 ) {
    sleep(1) ; // give file pages time to write
    system(" ./web-prep1.scr >> wp-log.txt 2>> wp-log.txt") ; // system
call 1 to make web pages
    sleep(1) ; // give files time to write
    system(" ./web-prep2.scr >> wp-log.txt 2>> wp-log.txt") ; // system
call 2 to make web pages
    sleep(1) ; // give files time to write
    system(" ./web-prep3.scr >> wp-log.txt 2>> wp-log.txt") ; // system
call 3 to make web pages
    sleep(1) ; // give files time to move
    system(" ./web-prep4.scr >> wp-log.txt 2>> wp-log.txt") ; // system
call 4 to make web pages
} else printf("\007 ##### WEB FILE PROBLEM - NEW WEB PAGES NOT GENERATED
#####\007\n");

printf("%s web done. Took: %u s, Probes: %u,filed: %u, Alarms: %u %u %u %u\n",
        &web_ts[14], time(NULL)-t_2 , n_scans,
n_scan_prt, n0, n1, n2, n3 );
    if( f_verbose || (bt != bt_old) || f_file ) {
        bt_old = bt ; // do every 15 minutes, not every 5 min
printf("  Pkts: %u, Flows in db: %u, Hosts in db: %u, cut: %u, Host Cut if < %u
byte, age > %u s\n",
        np, n_flow, n_host,
n_host_drop, host_cut, t_here - t_cut);
printf("  Thresholds. CI for Web-Local Page: %7u, - Web-Outside: %7u, for Alarm:
%7u.\n",
        web_alert0_0, web_alert1_0, *(&web_alert_2) ) ;
printf("  Thresholds. bps for Web-Local Page: %7u, - Web-Outside: %7u, for Alarm:
%7u b/s\n",
        (8* web_traf0_0)/300, (8*web_traf1_0)/300, *(&web_traf_2)) ;

printf("  CI Min. for Web. Inside: %u, Outside : %u", n0, n1) ;
printf("  Traffic Min. Inside: %u, Outside : %u\n", n2, n3) ;
printf("  Local hosts: %u - Foreign Hosts: %u. Probes Shown:
%u\n\n",nh,nf,n_scan_prt);

```

```

fflush( stdout ) ;
}

if((f_file) && (running == 1)) sleep(60) ; //delay to read web
if( f_verbose == 3) {printf(" WA Bottom. np:%u at %u\n", np, t_run) ; fflush(
stdout);}

return ;
} // end - web_alerts()

void read_thresholds( void ) {
    int h, x ;
    char s[80] ;
    FILE *lc_th_file, *lc_no_alarms_file, *lc_watch_list_file ;

    if((lc_th_file = fopen ("lc_thresholds.txt","rb"))==NULL) { // OPEN
lc_thresholds FILE
        printf("File 'lc_thresholds.txt' Can Not Be Opened to Read, t:
%u\n", * (&t_run)) ;
    }
    else {
        register unsigned int a, w, r, p ;
        a = web_alert_2 ;
        w = web_traf_2 ;
        r = restart_hour ;
        p = profile ;

        while( fscanf(lc_th_file,"%s\t%u\n", s, &x) != EOF ) {
            if( ! strcmp( s, "web_alert_2" ) ) web_alert_2 = x ;
            if( ! strcmp( s, "web_traf_2" ) ) web_traf_2 = x ;
            if( ! strcmp( s, "restart_hour" ) ) restart_hour = x ;
            if( ! strcmp( s, "profile" ) ) profile = x ;
        }

        if(( a != web_alert_2 )||( w != web_traf_2 )||( r != restart_hour
)||( p != profile )) {
            printf("### NEW VALUES: CI Alarm2: %u, Traf. Alarm: %u
(b/s), Restart: %u, Profile Action: %u\n",
web_alert_2, web_traf_2, restart_hour, profile);
        }
        fclose( lc_th_file ) ;
    } // end read threshhold file

    if((lc_no_alarms_file = fopen("lc_no_alarms.txt","rb"))==NULL) { // OPEN
lc_no_alarms.txt FILE
        printf("File 'lc_no_alarms.txt' Can Not Be Opened to Read, t: %u\n",
* (&t_run)) ;
    }
    else {
        unsigned int a1, a2, a3, a4, h, n_slot ;
        printf(" No-Alarm Set for:" ) ;

        while( fscanf(lc_no_alarms_file,"%u.%u.%u.%u\n", &a1, &a2, &a3, &a4)
!= EOF ) {
            h = (a1 << 24 ) | (a2 << 16) | (a3 << 8) | a4 ;
            if(n_slot = find_host( h, 1 ) ) {
                host[ n_slot ].alerts |= NO_ALARM ;
                printf(" %u.%u.%u.%u", a1, a2, a3, a4) ;
            }
        }
        printf("\n") ;
    }
}

```

```

                                LANcope Code
    fclose( lc_no_alarms_file ) ;
    } // end read threshold file

    if((lc_watch_list_file = fopen ("lc_watch_list.txt","rb"))==NULL) { //
OPEN lc_watch.txt FILE
        printf("File 'lc_watch_list.txt' Can Not Be Opened to Read, t:
%u\n", * (&t_run)) ;
    }
    else {
        unsigned int a1, a2, a3, a4, h, n_slot ;
        printf(" Watch_Host Set for:" ) ;

        while( fscanf(lc_watch_list_file,"%u.%u.%u.%u\n", &a1, &a2, &a3,
&a4) != EOF ) {
            h = (a1 << 24 ) | (a2 << 16) | (a3 << 8) | a4 ;
            if( n_slot = find_host( h, 1 ) ) {
                host[ n_slot ].alerts |= WATCH_HOST ;
                printf(" %u.%u.%u.%u", a1, a2, a3, a4) ;
            }
        }
        printf("\n") ;
        fclose( lc_watch_list_file ) ;
    } // end - file opened
    return ;
} // end of read_thresholds()

```

```

void services( unsigned int x ) { // puts list of services into serstr
    int n, j ;
    char *ptr ;

    n = 0 ; ptr = serstr ; serstr[0] = 0 ; // serstr-server list
    while(( x > 0) && (n < pn_max)) {
        if( x & 1) {
            sprintf(ptr,"%s ", port_name[ n ] ) ;
            ptr = & serstr[ strlen(serstr) ] ;
            if( strlen(serstr) > 380 ) {
                j = strlen(serstr) ;
                serstr[ j + 1 ] = 0 ;
                serstr[ j ] = '+' ;
                break ;
            }
        }
        n++ ; x = x >> 1 ;
    } // end while

    return ;
} // end services()

```

```

#ifdef CHECK_INDEX

```

```

unsigned long host_hash( unsigned long ip)
{ // returns host[i] unsigned Index, HOSTS MUST BE LOCKED
    unsigned long x, i, i_mark, n, index, scans_size = HOST_SLOTS ;

    x = ip ^ (ip << 6) ; /* make index from ip */
    index = x ;
    for (i = HOST_SHIFT ; i < 32 ; i += HOST_SHIFT ) {
        x = x >> HOST_SHIFT ;
        index ^= x ; // XOR bytes together
    }
    index = index & HOST_MASK ; // limit to right HOST_SHIFT bits
}

```



```

                                LANcope Code
index++ ;                      // index can be 1 to 2^N +1
    if( ! pthread_mutex_trylock( &mp_hosts ) ) {
printf(" ### host_hash() without mutex m_host being set. t: %u, Running:
%u\n",*(&t_run),running);
        pthread_mutex_unlock( &mp_hosts ) ;
    }

    if ( index >= HOST_SLOTS ) {
        printf("index bigger than HOST_SLOTS (%u > %u) at record %u\n",
index, HOST_SLOTS, *(&np));
        exit(-1) ;
    }
    return( index ) ; // end - host_hash (ony for CHECK_INDEX
}
#endif

int read_profiles( void ) { // ##### READ_PROFILES ( & BT[ ] )
#####
    FILE * profile ;
    long check ;
    unsigned long ip, h ;
    int n_pro = 0, n_table = 0, j, n_pts, n_hs ;
    struct stat file_info;
    unsigned char buffer[120] ;

    if( f_verbose == 3) {printf(" Read Profiles Start. np:%u at %u\n", np,
t_run) ; fflush( stdout);}
    if( stat("lc_profiles", &file_info) == 0 ) { // there is a file
        if((profile = fopen("lc_profiles","rb")) !=NULL) { // and it opened
            fread( (void *) &check, sizeof( long ), 1, profile) ;

            // 96 is number of bytes saved per host profile

            if( check != 96 ) {
                printf(" ### File lc_profiles ( %d )does not match
present host db structure size (96) ###\n",
                                check) ;
            }

            else { // check ok
                register int i ;
pthread_mutex_lock( &mp_hosts) ; // ### lock hosts[]
                while( 1 ) {
                    if( fread( (void *) &ip, sizeof( long ), 1,
profile) < 1)
                        break ;
                    if( (h = find_host( ip, 1 )) == 0 )
                        break ;
                    if( fread( (void *) &host[h].s_profile,
sizeof( long ), 1, profile) < 1 ) break ;
                    if( fread( (void *) &host[h].c_profile,
sizeof( long ), 1, profile) < 1 ) break ;
                    if( fread( (void *) &host[h].s_list[0],
sizeof( short ), 10, profile) < 10) break ;
                    if( fread( (void *) &host[h].c_list[0],
sizeof( short ), 10, profile) < 10) break ;
                    if( fread( (void *) &host[h].host_scan[0],
sizeof(long), 5, profile) < 5) break ;
                    if( fread( (void *) &host[h].scan_cntr[0],
sizeof(char), 4, profile) < 4) break ;
                    if( fread( (void *) &host[h].port_scan[0],
sizeof(long), 4, profile) < 4) break ;

```

LANcope Code

```

//if( f_verbose == 2 ) {
//    printf(" %8x  :%8x %8x :",host[h].ip, host[h].server, host[h].client
//);
//    for(i=0;i<10;i++) printf(" %u", host[h].s_list[i] );
//    printf(" :");
//    for(i=0;i<10;i++) printf(" %u", host[h].c_list[i] );
//    printf("\n");
//}
//    } // end while(1)
pthread_mutex_unlock( &mp_hosts); // ### unlock hosts[]
//    } // check ok
skip_profiles:
    fclose( profile );
    } // file opened ok
    } // stat -> end file-ok
//    if( f_verbose == 3) {printf(" Read Profiles Mid. np:%u at %u\n", np, t_run)
; fflush( stdout);}

    if( stat("lc_traf_table", &file_info) == 0 ) { // there is a file
        if((profile = fopen("lc_traf_table","rb")) != NULL) {
            fread( (void *) &check, sizeof( long ), 1, profile) ;
            if( check != sizeof( struct byte_table ) ) { // byte table
may change size due to revision
                printf(" ### File lc_traf_table ( %d )does not match
present bs[]. structure size! ###\n",
                    check) ;
            }
            else { // check is ok
                for( j = (TRAFFIC_VALUES - 1) ; j >= 0 ; j-- ) {
                    if( fread( (void *) &bs[j].t, check
1, profile) < 1 ) break ;
                    n_table++ ;
//if((f_verbose == 2) && bs[j].t) printf("j:%2d %5d %8d %8d %8d %8d\n",j,bs[j].t,
bs[j].bytes_in,
//                                bs[j].bytes_out,
bs[j].bytes_loc, bs[j].bytes_oo ) ;
                }
            } // end - 'check' is right
            fclose( profile );
        } // end - file opened ok
    } // end - there is a file
    bt = TRAFFIC_VALUES - 1 ;
    printf(" Read - Local Host Profiles: %d, Traf.Table Lines: %d\n", n_pro,
n_table ) ;
    // call save_profiles
    printf(" Active Locals: %d, n_host: %d\n", active_locals,
n_host ) ;
    // call save_profiles
    if( f_verbose == 3) {printf(" Read Profiles End. np:%u at %u\n", np, t_run)
; fflush( stdout);}
    return( n_pro ) ;
} // end read_profiles

int save_profiles( void ) { // ##### SAVE_PROFILES ( & BT[ ] )
#####
    FILE * profile ;
    long check ;
    unsigned long ip, hx ;
    int m, n_pro = 0, n_table=0, i, j ;
    if( f_verbose == 2) {printf(" Save Profiles Start. np:%u at %u\n", np, t_run) ;
fflush( stdout);}

```

```

LANcope Code
if((profile = fopen("lc_profiles","wb")) != NULL) {
    check = 96 ;
    fwrite( (void *) &check, sizeof( long ), 1, profile) ;

    for( hx = 1 ; hx < HOST_SLOTS ; hx++ ) { // save profiles of local
host
        if( host[hx].alerts & 0x1 ) {
            pthread_mutex_lock( &mp_hosts) ; // ### lock hosts[]
            if( fwrite( (void *) &host[hx].ip,          sizeof(
long ), 1, profile) < 1 ) break ;
            if( fwrite( (void *) &host[hx].s_profile, sizeof(
long ), 1, profile) < 1 ) break ;
            if( fwrite( (void *) &host[hx].c_profile, sizeof(
long ), 1, profile) < 1 ) break ;
            if( fwrite( (void *) &host[hx].s_list[0], sizeof(
short ), 10, profile) < 10 ) break ;
            if( fwrite( (void *) &host[hx].c_list[0], sizeof(
short ), 10, profile) < 10 ) break ;
            if( fwrite( (void *) &host[hx].host_scan[0],
sizeof(long), 5, profile) < 5 ) break ;
            if( fwrite( (void *) &host[hx].scan_cntr[0],
sizeof(char), 4, profile) < 4 ) break ;
            if( fwrite( (void *) &host[hx].port_scan[0],
sizeof(long), 4, profile) < 4 ) break ;
            n_pro++ ;
            if( f_verbose == 2 ) {
                printf(" %8x  :%8x %8x
",host[hx].ip, host[hx].server, host[hx].client ) ;
                for(i=0;i<10;i++) printf(" %u.",
host[hx].s_list[i] ) ;
                printf(" :");
                for(i=0;i<10;i++) printf(" %u.",
host[hx].c_list[i] ) ;
                printf("\n");
            }
            pthread_mutex_unlock( &mp_hosts) ; // ### unlock hosts[]
        } // end for(hx)
        fclose( profile ) ;
    }
    if( f_verbose == 3 ) {printf(" Save-Profiles Mid. np:%u at %u\n", np, t_run)
; fflush( stdout);}

    if((profile = fopen("lc_traf_table","wb"))!=NULL) {
pthread_mutex_lock( &mp_bs) ; // ### lock bs[]
        check = sizeof( struct byte_table ) ;
        fwrite( (void *) &check, sizeof( long ), 1, profile) ;
        m = bt ;
        m++ ;
        if( m > TRAFFIC_VALUES) m -= TRAFFIC_VALUES ; // prevents thread
sync problem
        for( j = 0 ; j < TRAFFIC_VALUES ; j++ ) { // j is counter, bs.[bt +
1] not reliable in this thread
            m-- ;
            if(m < 0 ) m += TRAFFIC_VALUES ; // m is index
            if( bs[m].t == 0 ) break ;
            if( fwrite( (void *) &bs[m].t, sizeof( struct byte_table ),
1, profile) < 1 ) break ;
            n_table++ ;
            //if((f_verbose == 2)&&(j==0)) printf("size:%d m:%2d  %11d  %8d %8d %8d %8d\n",
sizeof( struct byte_table ),
            m,bs[m].t, bs[m].bytes_in, bs[m].bytes_out,
bs[m].bytes_loc, bs[m].bytes_oo ) ;
        }
    }
}

```

LANcope Code

```

    }
    fclose( profile ) ; // break comes here
pthread_mutex_unlock( &mp_bs ) ; // ### unlock bs[]
}
printf(" Saved (at %u s) - Local Host Profiles: %d, Traf.Table Lines:
%d\n", t_run, n_pro, n_table ) ;
if( f_verbose == 3 ) {printf(" Save Profiles End. np:%u at %u\n", np, t_run)
; fflush( stdout);}
return( n_pro ) ;
} // end write_profiles

void record_probe( unsigned long hs, unsigned long d_ip, unsigned short des_port ) {
// sets bit map for ip-scan and port-scan detection
register int x1, unlock = 0 ; // mutex mp_hosts should be locked before
calling
register unsigned int m4, m2 ;

if( ( f_verbose == 2 ) || ( f_verbose == 3 ) ) {
printf(" Record-Probe Start. np:%u at %u, hs: %u, d_ip: %8x, port:
%u\n", np, *(&t_run), hs, d_ip, des_port);
fflush( stdout);
}

if( f_verbose == 2 ) printf(" ### SCAN hs: %u, da :%8x, ", hs, d_ip ) ;

x1 = (d_ip>>5) & 0x3 ; // index 0 to 3
m2 = (unsigned int) 1 << ( d_ip & 0x001f ) ; // 1 bit set in 32-bit field

if( ! (host[ hs ].host_scan[ x1 ] & m2) ) { // ----- check hscan128 bit
host[ hs ].host_scan[ x1 ] |= m2 ; // --- set bit for hscan128
host[hs].scan_cntr[1] ++ ;
}

m4 = (unsigned int) 1 << ( ( d_ip>>24 ) ^ ( d_ip>>16 ) ) & 0x001f ) ; // 1 bit
set in 32-bit field

if( ! (host[ hs ].host_scan[ 4 ] & m4) ) { // ----- check hscan32 bit
host[ hs ].host_scan[ 4 ] |= m4 ; // set bit for hscan32
host[hs].scan_cntr[0] ++ ;

if( host[hs].scan_cntr[0] > 24 ) { // clear once hscan32 is nearly
full
host[hs].host_scan[0] = host[hs].host_scan[1] = 0 ;
host[hs].host_scan[2] = host[hs].host_scan[3] =
host[hs].host_scan[4] = 0 ;
host[hs].scan_cntr[0] = host[hs].scan_cntr[1] = 0 ;
}

}

if( host[hs].scan_cntr[0] < (((3*host[hs].scan_cntr[1]) >> 3) - 2) ) { //
hscan32 < (3/8)hscan128 - 1
host[hs].alerts |= IP_SCAN ;
host[hs].concern += HOST_SCAN_CI ;
host[hs].host_scan[0] = host[hs].host_scan[1] = 0 ;
host[hs].host_scan[2] = host[hs].host_scan[3] =
host[hs].host_scan[4] = 0 ;
host[hs].scan_cntr[0] = host[hs].scan_cntr[1] = 0 ;

if( f_verbose == 2 ) printf(" ### BINGO p32: %u, p128:
%u\n", host[hs].scan_cntr[0], host[hs].scan_cntr[1]);
}

```

LANcope Code

```

else {
    if(( f_verbose == 2 ) && ( host[hs].scan_cntr[1] > 2 )) {
        printf(" --- NOGO h32: %u, h128: %u x32:%8x,
x128:%8x,%8x,%8x,%8x  x1:%d, x2:%8x\n",
        host[hs].scan_cntr[0], host[hs].scan_cntr[1],
        host[hs].host_scan[4],
        host[hs].host_scan[0], host[hs].host_scan[1],
        host[hs].host_scan[2], host[hs].host_scan[3], x1,m2);
    } }

    if( des_port < 1024 ) { // avoid false positives due to Napster
        register unsigned long pp, pm, pi ; // ##### PORT SCAN
DETECTION ##### //
        pp = des_port & 0x1f ; // 0 to 31
        pi = (des_port >> 5) & 1 ; // 0 or 1
        pm = (unsigned long) 1 << pp ; // 1 '1' in 32-bit field

        if(! (pm & host[ hs ].port_scan[ pi ])) { // new long-term bit to
set ?

short-term port scans    host[ hs ].port_scan[ pi ] |= pm ; // used to detect
                        host[hs].scan_cntr[2] ++ ;

                        if( host[hs].scan_cntr[2] > PORT_SCAN_MAX ) {
                            host[hs].concern += PORT_SCAN_CI ;
                            host[hs].alerts |= PT_SCAN_ALERT ;
                            host[hs].port_scan[0] = host[hs].port_scan[1] = 0 ;
// clear short-term port-scan bits & counter
                            host[hs].scan_cntr[2] = 0 ;
if(f_verbose == 2) printf(" ### Port Scan - Short-Term Detected. hs:%u\n",hs ) ;
                        }
                        } // end - ling-term threshold exceeded?
                    else {
                        if(f_verbose==2) {
                            printf("Port %u - ST bit already set. pi:%u, pp: %u,
pm: %8x, ST: %8x,%8x,LT: %8x-%8x\n\n",des_port, pi,pp,pm,
                            host[hs].port_scan[0], host[hs].port_scan[1],
                            host[hs].port_scan[2], host[hs].port_scan[3]);
                            fflush( stdout ) ;
                        }
                    }

                    if(! (pm & host[ hs ].port_scan[ pi | 2 ])) { // pi|2 = 2 or 3, new
long-term bit to set ?

long-term port scans    host[ hs ].port_scan[ pi | 2 ] |= pm ; // used to detect
                        host[hs].scan_cntr[3] ++ ;

                        if( host[hs].scan_cntr[3] > PORT_SCAN_LT_MAX ) {
                            host[hs].concern += PORT_SCAN_LT_CI ;
                            host[hs].alerts |= LT_PT_SCAN ;
                            host[hs].port_scan[2] = host[hs].port_scan[3] = 0 ;
// reset long-term port-scan bit map & counter
                            host[hs].scan_cntr[3] = 0 ;
if(f_verbose==2) printf(" ### Port Scan - Long-Term Detected. hs:%u\n",hs ) ;
                        }
                        } // end - ling-term threshold exceeded?
                    else {
                        if(f_verbose==2) {
                            printf("Port %u - LT bit already set. pi:%u, pp: %u,
pm: %8x, ST: %8x,%8x,LT: %8x-%8x\n\n",des_port, pi,pp,pm,

```

```

                                LANcope Code
                                host[hs].port_scan[0], host[hs].port_scan[1],
host[hs].port_scan[2], host[hs].port_scan[3]) ;
                                fflush( stdout ) ;
                                }
                                }
                                if( f_verbose == 3) {
                                printf(" Record-Probe End. np:%u at %u, hs: %u, d_ip: %8x,
port: %u\n",
                                np, *(&t_run) ,hs, d_ip, des_port);
                                fflush( stdout);
                                }
                                } // end - port scan check
                                return ;
} // - end - record_probe()

void suicide( int yesterday ) { // kill this instance of lancope, start fresh
    char command[50] ;

    // yesterday = (t_here % 86400) % 30 ;// day of month 0-29 - name of
directories for saving files
    setuid( 0 ) ;
    sprintf(command,"lc_restart.sh %d 1>> lc_log.txt 2>>lc_log.txt &",
yesterday) ;
    printf("system call : %s\n", command) ;
    if( system( command ) ) { // returns zero if ok
        printf(" ##### FAILED #####\n" ) ;
        return ;
    }
    printf(" ##### RESTART CALL OK, SHUTTING DOWN NOW ##### LOGS SAVED ON '%d'\n",
yesterday);
    running = 2 ; // end other threads if 'lc_restart' started.
    kill_tcpdump() ;
    return ;
} // end - suicide()

void userhandler(int sig) { // SIGTERM handler (kill <PID> response)
    int i ;
    i = save_profiles() ;
    printf("\n ##### SIGTERM (%d) - Saved %u Profiles. No Restart.
#####\n\n", sig, i ) ;
    running = 2 ;
    kill_tcpdump() ;
    return ;
} // end - userhandler

// ### END OF FILE #####

```